

15Amp. Superfast Plastic Rectifiers

MSR1560E2

$I_{F(AV)}$	15A
V_{RRM}	600V
I_{FSM}	150A
trr	30ns
T_j	175°C
$V_F(TYP)$	1.9V


Features

- 175°C operating junction temperature
- Glass passivated chip junction
- Low leakage current
- Superfast recovery time
- Low switching loss, high efficiency
- High forward surge capability
- High temperature soldering guaranteed : 260°C/40s, 0.25”(6.35mm) from case
- Pb-free lead plating package


Mechanical Data

- Case: TO-220AC molded plastic
- Mounting Position: Any
- Weight: 1.85 grams, 0.065 ounce approximately
- Terminals: Pure tin plated, solderable per J-STD-002 and JESD22-B102
- Epoxy: UL 94V-0 rate flame retardant
- Polarity : As marked.
- Mounting torque: 10 in.-lb. maximum

Equivalent Circuit



Outline



**Maximum Ratings and Electrical Characteristics**

(Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.)

Parameter	Symbol	Min.	Typ.	Max.	Units
Maximum Recurrent peak reverse voltage	V_{RRM}			600	V
Maximum RMS voltage	V_{RMS}			420	V
Maximum DC blocking voltage	V_{DC}			600	V
Maximum instantaneous forward voltage at $I_F=15A$	V_F		1.9	2.5	V
Maximum Average forward rectified current @ $T_C=100^\circ C$	$I_{F(AV)}$			15	A
Non-repetitive peak forward surge current @ 8.3ms single half sine wave superimposed on rated load (JEDEC method)	I_{FSM}			150	A
Maximum instantaneous reverse current at	I_R	$V_R=600V, T_C=25^\circ C$		10	μA
		$V_R=600V, T_C=125^\circ C$		500	
Maximum reverse recovery time	t_{rr}			30	ns
Typical junction capacitance @ $f=1MHz$ and applied 4V reverse voltage	C_J		46		pF
Storage temperature range	T_{stg}	-65		+175	$^\circ C$
Operating junction temperature range	T_J	-65		+175	$^\circ C$

Thermal Data


Parameter	Symbol	Value	Unit
Maximum Thermal Resistance, Junction-to-case	$R_{th,j-c}$	1.7	$^\circ C/W$
Maximum Thermal Resistance, Junction-to-ambient	$R_{th,j-a}$	60	$^\circ C/W$

Ordering Information


Device	Package	Shipping
MSR1560E2	TO-220AC (RoHS compliant package)	50 pcs / Tube, 40 Tubes/Box

Typical Characteristics


Forward Current Derating Curve




Forward Current vs Forward Voltage




Reverse Leakage Current vs Reverse Voltage



Junction Capacitance vs Reverse Voltage



TO-220AC Dimension



*:Typical

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.382	0.398	9.70	10.10	J	0.049	0.055	1.25	1.40
B	0.248	0.264	6.30	6.70	K	0.197	0.203	5.00	5.15
C	0.354	0.373	9.00	9.47	L	0.087	0.102	2.20	2.60
D	0.504	0.524	12.80	13.30	M	0.056	0.064	1.42	1.62
E	0.047	0.055	1.20	1.40	N	0.018	0.024	0.45	0.60
F	0.067*		1.70*		O	0.027	0.035	0.70	0.90
G	0.098*		2.50*		Φ	Φ0.142*		Φ3.60*	
H	0.118	0.134	3.00	3.40					

Notes: 1.Controlling dimension: millimeters.
 2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
 3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead: Pure tin plated
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.