

Part Number: C9042

Revision Date: 9/4/2012

4C 16 AWG 19/.0117 TC PVC / PVC



A. CONSTRUCTION

Conductor: #16 AWG 19/.0117 Tinned Copper
 Insulation: .016" Polyvinyl Chloride (PVC)
 Cable Core: Cable 4/C @ 3.25" LHL w/ clear polyester wrap, 100% coverage
 Jacket: ".032"" Polyvinyl Chloride (PVC) jacket
 Ripcord under Jacket"

DIAMETERS

.056" Nom
 .088" Nom
 .218" Nom
 .282" Nom

Print Legend: **CAROL® EXZEL™ -- C9042A -- 4C 16 AWG**
E105765-H (UL) TYPE CM 105C OR AWM 2464 80C 300V
VW-1 --- LL69381 CSA TYPE CMG 105C FT4 - CE --
-- ROHS -- MADE IN USA
(DATE CODE) (TRUMARK SEQUENTIAL FOOTAGE)

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

Temperature:	CM/CMG: 105C, AWM: 80C
Suggested Working Voltage:	300V
Conductor DCR:	4.19 Ohms/M' @ 20°C
Mutual Capacitance:	27.4 pF/ft. @ 1 kHz Nom

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	RED
3	WHITE
4	GREEN