


Metal Core SMD Power Inductors (MCOIL(TM) MD series)

MDKK1616T3R3MM



■ Features

- Item Summary
3.3 μ H(\pm 20%), 1150mA, 650mA
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping 2500pcs

■ Products characteristics table

CaseSize (EIA/JIS)	-/1616
Inductance	3.3 μ H(\pm 20%)
Inductance Measuring Frequency	1MHz
Rated Current -Saturation Current	1150mA
Rated Current -Temperature Rise Current	650mA
DC Resistance (max)	0.515 Ω
Avg. of DC.Resistance	0.45 Ω
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow

■ External Dimensions

L	1.64mm \pm 0.1
W	1.64mm \pm 0.1
H	1mm max

■ Recommended Land Patterns

【推奨ランドパターン】
実装上の注意
・実装仕様を確認の上ご使用ください。また、本製品はハンダ付はリフローはんだ工法にのみ対応します。

【Recommended Land Pattern】
Surface Mounting
*Mounting and soldering conditions should be checked beforehand.
*Applicable soldering process to these products is reflow soldering only.



Metal Core SMD Power Inductors (MCOIL_{TM} MD series)

Type	A	B	C
1616	0.50	0.60	1.65
2020	0.65	0.70	2.00
3030	0.80	1.40	2.70
4040	1.20	1.60	3.70
5050	1.50	2.10	4.00

unit:mm

2015.02.25

The data is reference only. Electrical characteristics vary depending on environment or measurement condition. TAIYO YUDEN reserves the right to make change to the Date at any time without notice. Before making final selection, please check product specification.