

Product Summary

Device	$V_{(BR)DSS}$	$R_{DS(ON) \max}$	$I_D \max$ $T_A = 25^\circ\text{C}$
Q1	20V	0.5Ω @ $V_{GS} = 4.5\text{V}$	1030mA
		0.9Ω @ $V_{GS} = 1.8\text{V}$	740mA
Q2	-20V	1.0Ω @ $V_{GS} = -4.5\text{V}$	-700mA
		2.0Ω @ $V_{GS} = -1.8\text{V}$	-460mA

Description and Applications

This new generation MOSFET has been designed to minimize the on-state resistance ($R_{DS(on)}$) and yet maintain superior switching performance, making it ideal for high efficiency power management applications.


- Power management functions
- Battery Operated Systems and Solid-State Relays
- Load switch

Features and Benefits

- Low On-Resistance
- Low Gate Threshold Voltage $V_{GS(th)} < 1\text{V}$
- Low Input Capacitance
- Fast Switching Speed
- Low Input/Output Leakage
- Complementary Pair MOSFET
- Ultra-Small Surface Mount Package
- **ESD Protected Gate to 2kV HBM**
- **Lead Free/RoHS Compliant (Note 1)**
- **"Green" Device, Halogen and Antimony Free (Note 2)**
- **Qualified to AEC-Q101 Standards for High Reliability**

Mechanical Data

- Case: SOT563
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminal Connections: See Diagram
- Terminals: Finish – Matte Tin annealed over Copper leadframe. Solderable per MIL-STD-202, Method 208
- Weight: 0.003 grams (approximate)




Ordering Information (Note 3)

Part Number	Case	Packaging
DMC2400UV-7	SOT563	3000/Tape & Reel
DMC2400UV-13	SOT563	10000/Tape & Reel

- Notes:
1. EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant. No purposely added lead. Halogen and Antimony free
 2. Diodes Inc.'s "Green" policy can be found on our website at <http://www.diodes.com>.
 3. For packaging details, go to our website at <http://www.diodes.com>.

Marking Information



CA3 = Product Type Marking Code
 YM = Date Code Marking
 Y = Year (ex: Y = 2011)
 M = Month (ex: 9 = September)

Date Code Key

Year	2011	2012	2013	2014	2015	2016	2017
Code	Y	Z	A	B	C	D	E

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

Maximum Ratings - Q1 N-CHANNEL @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic			Symbol	Value	Units
Drain-Source Voltage			V_{DSS}	20	V
Gate-Source Voltage			V_{GSS}	± 12	V
Continuous Drain Current (Note 5) $V_{GS} = 4.5\text{V}$	Steady State	$T_A = 25^\circ\text{C}$ $T_A = 70^\circ\text{C}$	I_D	1030 800	mA
	$t < 10\text{s}$	$T_A = 25^\circ\text{C}$ $T_A = 70^\circ\text{C}$	I_D	1150 900	mA
Continuous Drain Current (Note 5) $V_{GS} = 1.8\text{V}$	Steady State	$T_A = 25^\circ\text{C}$ $T_A = 70^\circ\text{C}$	I_D	740 570	mA
	$t < 10\text{s}$	$T_A = 25^\circ\text{C}$ $T_A = 70^\circ\text{C}$	I_D	870 700	mA
Pulsed Drain Current (10 μs pulse, duty cycle = 1%)			I_{DM}	3	A
Maximum Body Diode continuous Current			I_S	800	mA

Maximum Ratings - Q2 P-CHANNEL @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic			Symbol	Value	Units
Drain-Source Voltage			V_{DSS}	-20	V
Gate-Source Voltage			V_{GSS}	± 8	V
Continuous Drain Current (Note 5) $V_{GS} = -4.5\text{V}$	Steady State	$T_A = 25^\circ\text{C}$ $T_A = 70^\circ\text{C}$	I_D	-700 -550	mA
	$t < 10\text{s}$	$T_A = 25^\circ\text{C}$ $T_A = 70^\circ\text{C}$	I_D	-820 -640	mA
Continuous Drain Current (Note 5) $V_{GS} = -1.8\text{V}$	Steady State	$T_A = 25^\circ\text{C}$ $T_A = 70^\circ\text{C}$	I_D	-460 -350	mA
	$t < 10\text{s}$	$T_A = 25^\circ\text{C}$ $T_A = 70^\circ\text{C}$	I_D	-550 -420	mA
Pulsed Drain Current (10 μs pulse, duty cycle = 1%)			I_{DM}	-2	A
Maximum Body Diode continuous Current			I_S	-800	mA

Thermal Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic		Symbol	Value	Units
Total Power Dissipation (Note 4)		P_D	0.45	W
Thermal Resistance, Junction to Ambient (Note 4)	Steady state	$R_{\theta JA}$	281	$^\circ\text{C/W}$
	$t < 10\text{s}$		210	$^\circ\text{C/W}$
Total Power Dissipation (Note 5)		P_D	1	W
Thermal Resistance, Junction to Ambient (Note 5)	Steady state	$R_{\theta JA}$	129	$^\circ\text{C/W}$
	$t < 10\text{s}$		97	$^\circ\text{C/W}$
Operating and Storage Temperature Range		T_J, T_{STG}	-55 to +150	$^\circ\text{C}$

Electrical Characteristics - Q1 N-CHANNEL @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 6)						
Drain-Source Breakdown Voltage	BV_{DSS}	20	-	-	V	$V_{GS} = 0V, I_D = 1mA$
Zero Gate Voltage Drain Current $T_J = 25^\circ\text{C}$	I_{DSS}	-	-	100	nA	$V_{DS} = 20V, V_{GS} = 0V$
Gate-Source Leakage	I_{GSS}	-	-	± 1	μA	$V_{GS} = \pm 5V, V_{DS} = 0V$
		-	-	± 4.0		$V_{GS} = \pm 8V, V_{DS} = 0V$
ON CHARACTERISTICS (Note 6)						
Gate Threshold Voltage	$V_{GS(th)}$	0.5	-	0.9	V	$V_{DS} = V_{GS}, I_D = 250\mu A$
Static Drain-Source On-Resistance	$R_{DS(on)}$	-	0.3	0.48	Ω	$V_{GS} = 5.0V, I_D = 200mA$
		-	0.35	0.5		$V_{GS} = 4.5V, I_D = 200mA$
		-	0.45	0.7		$V_{GS} = 2.5V, I_D = 200mA$
		-	0.55	0.9		$V_{GS} = 1.8V, I_D = 100mA$
		-	0.65	1.5		$V_{GS} = 1.5V, I_D = 50mA$
		-	2	-		$V_{GS} = 1.2V, I_D = 1mA$
		-	-	-		-
Forward Transfer Admittance	$ Y_{fs} $	-	1.4	-	S	$V_{DS} = 3V, I_D = 200mA$
Diode Forward Voltage	V_{SD}	-	0.7	1.2	V	$V_{GS} = 0V, I_S = 500mA$
DYNAMIC CHARACTERISTICS (Note 7)						
Input Capacitance	C_{iss}	-	37.1	-	pF	$V_{DS} = 10V, V_{GS} = 0V, f = 1.0MHz$
Output Capacitance	C_{oss}	-	6.5	-		
Reverse Transfer Capacitance	C_{rss}	-	4.8	-		
Gate Resistance	R_g	-	68	-	Ω	$V_{DS} = 0V, V_{GS} = 0V$
Total Gate Charge	Q_g	-	0.5	-	nC	$V_{GS} = 4.5V, V_{DS} = 10V, I_D = 250mA$
Gate-Source Charge	Q_{gs}	-	0.07	-		
Gate-Drain Charge	Q_{gd}	-	0.1	-		
Turn-On Delay Time	$t_{D(on)}$	-	4.06	-	ns	$V_{DD} = 10V, V_{GS} = 4.5V, R_L = 47\Omega, R_G = 10\Omega, I_D = 200mA$
Turn-On Rise Time	t_r	-	7.28	-		
Turn-Off Delay Time	$t_{D(off)}$	-	13.74	-		
Turn-Off Fall Time	t_f	-	10.54	-		

- Notes:
4. Device mounted on FR-4 substrate PC board, 2oz copper, with minimum recommended pad layout.
 5. Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.
 6. Short duration pulse test used to minimize self-heating effect.
 7. Guaranteed by design. Not subject to product testing.




Fig. 1 Typical Output Characteristics




Fig. 2 Typical Transfer Characteristics




Fig. 3 Typical On-Resistance vs. Drain Current and Gate Voltage




Fig. 4 Typical Drain-Source On-Resistance vs. Drain Current and Temperature




Fig. 5 On-Resistance Variation with Temperature




Fig. 6 On-Resistance Variation with Temperature




Fig. 7 Gate Threshold Variation vs. Ambient Temperature










Fig. 8 Diode Forward Voltage vs. Current



Electrical Characteristics - Q2 P-CHANNEL @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 6)						
Drain-Source Breakdown Voltage	BV_{DSS}	-20	-	-	V	$V_{GS} = 0V, I_D = -1mA$
Zero Gate Voltage Drain Current $T_J = 25^\circ\text{C}$	I_{DSS}	-	-	-100	nA	$V_{DS} = -20V, V_{GS} = 0V$
Gate-Source Leakage	I_{GSS}	-	-	± 1.0	μA	$V_{GS} = \pm 5V, V_{DS} = 0V$
		-	-	± 5.0		$V_{GS} = \pm 8V, V_{DS} = 0V$
ON CHARACTERISTICS (Note 6)						
Gate Threshold Voltage	$V_{GS(th)}$	-0.5	-	-1.0	V	$V_{DS} = V_{GS}, I_D = -250\mu\text{A}$
Static Drain-Source On-Resistance	$R_{DS(on)}$	-	0.67	0.97	Ω	$V_{GS} = -5V, I_D = -100mA$
		-	0.7	1.0		$V_{GS} = -4.5V, I_D = -100mA$
		-	0.9	1.5		$V_{GS} = -2.5V, I_D = -80mA$
		-	1.2	2.0		$V_{GS} = -1.8V, I_D = -40mA$
		-	1.5	3.0		$V_{GS} = -1.5V, I_D = -30mA$
		-	5	-		$V_{GS} = -1.2V, I_D = -1mA$
Forward Transfer Admittance	$ Y_{fs} $	-	0.7	-	S	$V_{DS} = -3V, I_D = -100mA$
Diode Forward Voltage	V_{SD}	-	-0.75	-1.2	V	$V_{GS} = 0V, I_S = -330mA$
DYNAMIC CHARACTERISTICS (Note 7)						
Input Capacitance	C_{iss}	-	46.1	-	pF	$V_{DS} = 10V, V_{GS} = 0V, f = 1.0MHz$
Output Capacitance	C_{oss}	-	7.2	-		
Reverse Transfer Capacitance	C_{rss}	-	4.9	-		
Gate Resistance	R_g	-	14.3	-	Ω	$V_{DS} = 0V, V_{GS} = 0V,$
Total Gate Charge $V_{GS} = -4.5V$	Q_g	-	0.5	-	nC	$V_{DS} = -10V, I_D = -250mA$
Total Gate Charge $V_{GS} = -10V$	Q_g	-	0.85	-		
Gate-Source Charge	Q_{gs}	-	0.09	-		
Gate-Drain Charge	Q_{gd}	-	0.09	-		
Turn-On Delay Time	$t_{D(on)}$	-	8.5	-	ns	$V_{DD} = -3V, V_{GS} = -2.5V, R_L = 300\Omega, R_G = 25\Omega, I_D = -100mA$
Turn-On Rise Time	t_r	-	4.3	-		
Turn-Off Delay Time	$t_{D(off)}$	-	20.2	-		
Turn-Off Fall Time	t_f	-	19.2	-		

- Notes: 4. Device mounted on FR-4 substrate PC board, 2oz copper, with minimum recommended pad layout.
 5. Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.
 6. Short duration pulse test used to minimize self-heating effect.
 7. Guaranteed by design. Not subject to product testing.






Fig. 15 Typical On-Resistance vs. Drain Current and Gate Voltage




Fig. 16 Typical On-Resistance vs. Drain Current and Temperature




Fig. 17 On-Resistance Variation with Temperature




Fig. 18 On-Resistance vs. Temperature




Fig. 19 Gate Threshold Variation vs. Ambient Temperature




Fig. 20 Diode Forward Voltage vs. Current




Fig. 21 Typical Junction Capacitance




Fig. 22 Typical Drain-Source Leakage Current vs. Voltage




Fig. 23 Gate-Charge Characteristics




Fig. 24 SOA, Safe Operation Area






Fig. 25 Transient Thermal Response

Package Outline Dimensions



SOT563			
Dim	Min	Max	Typ
A	0.15	0.30	0.20
B	1.10	1.25	1.20
C	1.55	1.70	1.60
D	-	-	0.50
G	0.90	1.10	1.00
H	1.50	1.70	1.60
K	0.55	0.60	0.60
L	0.10	0.30	0.20
M	0.10	0.18	0.11
All Dimensions in mm			

Suggested Pad Layout



Dimensions	Value (in mm)
Z	2.2
G	1.2
X	0.375
Y	0.5
C1	1.7
C2	0.5

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2012, Diodes Incorporated

www.diodes.com