



Directional 10 dB SMA Coupler From 500 MHz to 18 GHz Rated To 30 Watts

TECHNICAL DATA SHEET

PE2243-10

Configuration

Connector 1	SMA Female
Connector 2	SMA Female
Coupled Connectors	SMA Female
Design	Directional Coupler

Electrical Specifications (Values at 25°C, sea level)

Description	Minimum	Typical	Maximum	Units
Frequency Range	0.5		18	GHz
Directivity	20			dB
Impedance		50		Ohms
Insertion Loss			2.06	dB
Input Power			30	Watts
Input VSWR			1.37:1	
Peak Power			3	KWatts
Coupling Value		10		dB
Coupling Tolerance			± 1.25	dB
Frequency Sensitivity		1		dB

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Range	0.5 to 4	4 to 8	8 to 12.4	12.4 to 18		GHz
Insertion Loss	0.96	1.16	1.6	2.06		dB
VSWR	1.22	1.22:1	1.28:1	1.37:1		

Mechanical Specifications

Size

Length	5.15 in [130.81 mm]
Width/Dia.	0.38 in [9.65 mm]
Height	1.11 in [28.19 mm]

Connectors

Description	Connector 1	Connector 2	Coupled Connectors
Type	SMA Female	SMA Female	SMA Female

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Directional 10 dB SMA Coupler From 500 MHz to 18 GHz Rated To 30 Watts PE2243-10](#)



Directional 10 dB SMA Coupler From 500 MHz
to 18 GHz Rated To 30 Watts

TECHNICAL DATA SHEET

PE2243-10

Compliance Certifications (visit www.Pasternack.com for current document)
RoHS Compliant

Plotted and Other Data

Notes:

- Values at 25 °C, sea level

Outline Drawing




FIGURE 1

P/N	ATTEN.	FIGURE
PE2243-10	10 dB	1
PE2243-20	20 dB	1
PE2243-30	30 dB	1

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Directional 10 dB SMA Coupler From 500 MHz to 18 GHz Rated To 30 Watts PE2243-10](#)





Directional 10 dB SMA Coupler From 500 MHz to 18 GHz Rated To 30 Watts

TECHNICAL DATA SHEET

PE2243-10

Directional 10 dB SMA Coupler From 500 MHz to 18 GHz Rated To 30 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Directional 10 dB SMA Coupler From 500 MHz to 18 GHz Rated To 30 Watts PE2243-10](http://www.pasternack.com/directional-10-db-sma-coupler-500-mhz-18-ghz-30-watts-pe2243-10-p.aspx)

URL: <http://www.pasternack.com/directional-10-db-sma-coupler-500-mhz-18-ghz-30-watts-pe2243-10-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.