

**MATERIALS**

CONNECTOR	BRASS NICKEL PLATED
CONTACT	GOLD PLATED
INSULATOR	PTFE
HEAT SINK	ANODIZED ALUMINUM



HEAT SINK

LENGTH = 12.000"  
 HEIGHT = 6.250"  
 WIDTH = 6.250"

SPECIFICATIONS

FREQUENCY RANGE: DC TO 500 MHz  
 ATTENUATION: 2 dB  
 IMPEDANCE: 50 OHMS  
 ACCURACY: ±.5 dB  
 VSWR: 1.15:1 MAXIMUM  
 RF INPUT POWER: 500 WATT AVERAGE AT 25°C  
 DERATED TO 250 WATTS AT 100°C



**PASTERNACK ENTERPRISES, INC.**

P.O BOX 16759, IRVINE, CA 92623  
 PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: [www.pasternack.com](http://www.pasternack.com)  
 E-MAIL ADDRESS: [sales@pasternack.com](mailto:sales@pasternack.com)

**COAXIAL & FIBER OPTICS**

DWG TITLE

**PE7032-2**

DES.

N ATTENUATOR MALE TO FEMALE 500 WATT,  
 FREQUENCY RANGE: DC TO 500 MHz

SIZE A

**FSCM NO. 53919**

CAD FILE

072902

SCALE N/A

127

**NOTES:**

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.