

Precision 2.4mm Female to N Male Adapter



TECHNICAL DATA SHEET

Precision 2.4mm Female to N Male Adapter	
Configuration Connector 1 Impedance 1 Connector Specification 1 Connector 2 Impedance 2 Connector Specification 2 Adapter Design Body Style	2.4mm Female 50 Ohms MIL-STD-348 N Male 50 Ohms MIL-STD-348 Precision Straight
Electrical Specifications Frequency Range, GHz Maximum VSWR	DC to 18 1.15:1
Mechanical Specifications	
Temperature Operating Range,deg C	-65 to +125
Size Length, in [mm] Width/Dia., in [mm]	1.715 [43.56] 0.8 [20.32]
Connector 1	
Type Inner Conductor Material and Plating Body Material and Plating	2.4mm Female Beryllium Copper, Gold Passivated Stainless Steel
Connector 2	
Type Inner Conductor Material and Plating Body Material and Plating	N Male Beryllium Copper, Gold Passivated Stainless Steel
Compliance Certifications (visit www.Pasternack.com RoHS Compliant	for current document) Yes
Plotted and Other Data Notes:	Values at 25 °C, sea level
URL: http://www.pasternack.com/2.4mm-female-n-mal	e-straight-adapter-pe9503-p.aspx
•	Enterprises has same day shipment for domestic and International ain a 99% availability and are part of the broadest selection in the

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



industry.

PE9503

PE9503 CAD Drawing Precision 2.4mm Female to N Male Adapter

