

BPF-3319-Z

19" Fanless Panel PC with Touch Screen, Atom™ N270, 2W Stereo Speaker, CCD Camera
6 COM, 6 USB, 12V DC Adapter

Panel PC



Features

- » Fanless, aluminum front panel design
- » 19" TFT color panel display w/ touch screen
- » Intel® Atom™ N270 processor
- » VGA, Gigabit Ethernet, Audio port
- » 2W Stereo Speaker
- » CCD Camera
- » 2 x 2.5" SATA HDD space, 1 x slim CD-ROM space
- » 1 x CF, 1 x mini PCI socket
- » 6 x COM port, 6 x USB2.0 port
- » COM port voltage output
- » 12V DC adapter
- » Option for Wireless LAN module

System

LCD

Size: 19"
Max. Resolution: 1280 x 1024 pixels
Brightness: 300 cd/m²
Contrast Ratio: 800:1
Max. Color: 16.7M colors/RGB 8-bits
Pixel Pitch: 0.098 x 0.294 mm

Touch Screen

19" resistive

SBC

HS-8601

CPU

Intel® Atom™ N270 processor 1.6GHz

System Chipset

Intel® 945GSE/ICH7-M

System Memory

1 x 200-pin SO-DIMM, DDR2 533MHz, Max. 2GB

Display Interface:

1 x D-SUB 15-pin
1 x Brightness controller for CCFL
1 x CCD Camera

Audio Interface

Audio jack for MIC In, Line Out
2W Amplifier with Stereo Speaker

Ethernet Interface

1 x RJ-45 for Gigabit Ethernet
1 x mini PCI wireless LAN module (option)

Storage

2 x 2.5" SATA HDD space
1 x slim CD-ROM space
1 x Type II CF socket

Expansion Interface

1 x Type III mini PCI socket

Watchdog Timer

Software programmable time-out intervals from
1~255 sec. or 1~255 min.

H/W Status Monitor

Monitoring temperatures, voltages status

Power

12V 84W DC adapter with lockable jack

Operating/Storage Temperature

0~45°C/-20~+70°C

Certification

FCC/CE Class A compliance
IP65 front panel protection compliance


Dimensions

48.0(L) x 38.0(H) x 6.02(W) cm


Cut Out Size

43.4(L) x 34.9(H) cm

I/O Interface



Dimensions (unit:cm)



Ordering Information

BPF-3319-Z

19" Panel PC w/Touch Screen, Atom™ 1.6GHz CPU,
2W Stereo Speaker, CCD Camera, 6 COM, 6 USB,
12V DC Adapter

Accessory Options

Table Top Metal Stand, Memory Module, CF Module,
Wireless LAN Module, 2.5" SATA HDD, Slim CD-ROM