

## SPECIFICATTON FOR APPROVAL

**CUSTOMER NAME:** \_\_\_\_\_

**PRODUCT NAME:** Surge Absorber

**HUAXINAN P/N :** \_\_\_\_\_

**CUSTOMER P/N :** \_\_\_\_\_

### Customer

Manufacturing Department: \_\_\_\_\_

Quality Assurance Department: \_\_\_\_\_

Engineering Department: \_\_\_\_\_

company seal:

### Supplier

Manufacturing Department: Lui Wei

Quality Assurance Department: Wei Yu

Engineering Department: wang qing

company seal:

**TEL : +86 - 755- 27465585**

**Fax : +86 - 755- 27270662**

**Email: sales@huaandz.com**

**abc0734@126.com**

**Address:4th Floor,Building 5,Alley2,ZhongWu New District,XiXiang Town,BaoAn District,  
ShenZhen ,China**

**Web: www.huaandz.com**

**1 Application:**
**Fast Delivery Time**


- For instantaneous over-voltage protection to ADSL,ISDN,MODEM,FAX,TEL,Power Supplies,Alarm systems.
- For instantaneous over-voltage protection to RS485,RS232 port, CATV,video transceiver.
- For instantaneous over-voltage protection to ammeter,water meter auto admin system, etc

**2 Features**

- Small capacitance and excellent insulation resistance(100MΩ min).
- Small size,No polarity.No dark effect.
- Low electrode capacitance(1pF max).
- Quick response for electrostatic,surge voltage and low limiting voltage.
- Stable for repeated discharge test conditions.
- Operating temperature: -40℃ ~ +85℃. Storage temperature: -40℃ ~ +125℃.

**3 Electrical Characteristics**

Part Number	DC Spark-Over Voltage Vs(V)		Insulation Resistance		Capacitance of electrostatic 1KHz-6V(PF)	Surge current capacity 8/20us	Surge Life Test
	Nominal value	(min-max)	Test voltage	IR (MΩ)			
<b>HAB-141N</b>	140V	(98V-182V)	DC50V	>100MΩ	1PF(MAX)	1000A	1KHz-10KV Max (10/700us 4KV 100A 10times)
<b>HAB-181N</b>	180V	(126V-234V)	DC100V				
<b>HAB-201M</b>	200V	(160V-240V)					
<b>HAB-301M</b>	300V	(240V-360V)	DC250V				
<b>HAB-401M</b>	400V	(320V-480V)					
<b>HAB-501M</b>	500V	(400V-600V)	DC400V				
<b>HAB-601M</b>	600V	(480V-720V)					
<b>HAB-901M</b>	900V	(750V-1050V)	DC500V				
<b>HAB-102M</b>	1000V	(800V-1200V)					

**4 Dimension(Diameter 2.6mm , Length 5.0mm)**


**5 Marking of colour code:**

**Fast Delivery Time**

NO



**HAB Series Photo**

**6 Part Number System (型号构成) :**

Example      **HAB**      —      **301**      —      **M**  
                     ①                                      ②                                      ③

No	Symbols Explain
① Series Name	HAB series    Glass Tube Dimension :Diameter: $\phi 2.6\text{mm}$ , Length: 5.0mm
② Nominal DC spark over voltage	The symbol denoting nominal DC spark over voltage shall be expressed by three numerals.The first and second numerals shall represent the significant figures of nominal DC spark over voltage in volts(V),and the third numerals shall represent the number of zeros ,following the significant figures. Example) 301—— $30 \times 10^1 = 300$
③ Tolerances of DC Spark over Voltage	Tolerances: L — $\pm 15\%$ ; M — $\pm 20\%$ ; N — $\pm 30\%$ ;



7 Initial Characteristics 基本特性 :

项目 Test Item	测试条件 Test Method	规格值 Specification
直流感电电压 DC Spark-Over VoltageVs(V)	逐渐地增加测量使用直流电压, 即可知其开始电压, 测定电流为一毫安与测定时间最大为一秒 (1sec).(1mA) (Add and measure the DC Voltage gradually Maxto get the discharge threshold voltage. The measuring current is 1mA/1 second max.)	依型号而定 (It depends on each part number.)
内绝缘电阻 Insulation Resistance	在规定的设定直流电压下, 跨在两端引线, 即测量其内绝缘电阻值.(Measure the insulation resistance of two end of leadwire under the specified DC voltage.)	100MΩ或大于 100MΩ (100MΩ min.)
静电电容 Capacitance C(pF)	使用频率 1KHZ 与小于或等于 6V 直流电压之电源, 即测量其静电电容量 Measure the Electrostatic Capacitance under the test condition of 1KHz,DC 6V(max).	1PF 或小于 1PF (1pF max.)

8 Enviromental Characteristics(环境试验) :

试验项目 Test Item	试验方法 Test Method	性能 Characteristics
耐寒性(依据 JIS C0020) Cold Resistance JIS C0020	放置于-40℃±3℃之环境中 1000 小时后,取出置于常温常湿中 4 小时后,检测直流开始放电电压, 绝缘阻抗, 静电容量及检查外观. After -40±3℃(1000hrs) / room temp.,normal humidity(4 hrs) cycle,measure the properties.	满足各个特性之规格值 Within standard mentioned in Initial Characteristics.
耐热性(依据 JIS C0021) Heat Resistance JIS C0021	放置于 125℃±2℃之环境中 1000 小时后,取出置于常温常湿中 4 小时后,检测直流开始放电电压, 绝缘阻抗, 静电容量及检查外观. After 125±2℃(1000hrs) / room temp.,normal humidity(4 hrs) cycle,measure the properties.	满足各个特性之规格值 Within standard mentioned in Initial Characteristics.
耐湿性(依据 JIS C0022) Humidity Resistance JIS C0020	放置于 85℃±2℃ RH85%之环境中 1000 小时后,取出置于常温常湿中 4 小时后,检测直流开始放电电压, 绝缘阻抗, 静电容量及检查外观。 After 85±2℃, 85% RH (1000hrs)/room temp., normal humidity (4hrs)cycle, measure the properties.	满足各个特性之规格值 Within standard mentioned in Initial Characteristics.
温度周期(依据 JISC0025) Temperature Cycle Test (JIS C0025)	-40℃±3℃(30 分)~(常温 3 分)~125℃±2℃(30 分)为 1 周期,重复 25 次后,取出置于常温常湿中 4 小时后,检测直流开始放电电压, 绝缘阻抗, 静电容量及检查外观。 25 times repetition of cycle -40±3℃ (30 Min.),roon temp., (4 Min.),125±2℃(30 Min.),room temp., normal humidity(4hrs) .	满足各个特性之规格值 Within standard mentioned in Initial Characteristics.

## 9 Solder Characteristics 焊锡特性 :

试验项目 Test Item	试验方法 Test Method	结果 Result
焊锡附着性 (依据 JIS C0050 4.6 项) Solderability (JIS C0050,4.6)	将沾过助焊剂之导线, 自距离导线熔接点根部 3mm 处起, 浸于 265±5℃之焊锡液中 5 秒钟后, 将导线之助焊剂洗净后, 检查焊锡附着情形.(Apply flux and immerse in molten solder, up to the point of 3mm from the body,for 5 sec. (265℃±5℃). Wash the leadwire and check for soldering adhesion.)	導線須均勻附著 90%上. (Lead wire is evenly covered by solder over 90%.)
焊锡耐热性 (依据 JISC0051) Solder Heat (JIS C0051)	将沾过助焊剂之导线, 自距离导线熔接点根部 2mm 处起, 浸于 265±5℃之焊锡液中 10 秒钟后,检测直流开始放电电压,绝缘阻抗,静电容量及检查外观. (Lead wire is dipped up to the point of 2mm from the body, into 265℃±5℃ solder.for 10±1 sec.And measure the properties.)	满足各個特性之规格值 Within standard mentioned in Initial Characteristics.

## 10 Surge Characteristics 突波特性 :

试验项目 Test Item	试验方法 Test Method	结果 Result
突波寿命(HAB) Life(HAB)	将(10X700)µsec-1KV 突波,变换极向各 5 次,(100X1000)µsec-1KV 之突波,变换极向各 6 次,每隔 30 秒施加于试料 24 次后,检测直流开始放电电压,绝缘阻抗,静电容量及检查外观 (Apply a standard impulse voltage (10X700)µsec)of 1KV for 5 times with intervals of 30 sec., and then change the polarity of the surge and apply a impulse again. And similarly, apply a impulse voltage((100X1000)µsec) of 1KV. Total apply 24 times. Then measure DC spark-over voltage, IR & Capacitance.)	直流开始放电电压 HAB △Vs/Vs≦30% (DC sparkover volatage HAB: △Vs/Vs≦30%)
突波寿命(HAB) Life(HAB)	每间隔 10 秒施加 10KV 之电压于 1500PF 之电容器通过试料,做 200 次(Apply 10 KV voltage charged in 1500pF condenser and apply the current to the specimen,200 times at 10 seconds of intervals.)	绝缘阻抗和静电电容:须满足规定值 外观:无影响使用之显著缺陷 (Insulation Resistance & Capacitance to meet the specified value.Appearance: No cracks or failures .)