

P-tec Corp. Tel:(866) 695 4162
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa CO 81101 Fax:(719) 589 3592
 www.p-tec.net



PL321 Series 3mm LED Panel Mount Metal Holder

Features

- *Panel Mount Indicator with Outer Reflector
- *Chrome or Black Finish
- *Mounting Hole 6 mm (0.236")
- *Mounting Hardware Included
- *1 Yellow LED with Color Diffused Lens used
- *Standard Terminals
- *RoHS Compliant

Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

| | |
|--|--------------------|
| Power Dissipation..... | 78mW |
| Reverse Voltage (<100 μ A)..... | 5.0V |
| Max Forward Current..... | 30mA |
| Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)..... | 100mA |
| Operating Temperature Range..... | -25°C to +85°C |
| Storage Temperature Range..... | -40°C to +100°C |
| Soldering Temperature (1.6 mm below body)..... | 260° for 5 seconds |

Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

| Part Number Add S for Chrome Finish Add B for Black Finish | Emitting Color | Chip Material | Peak Wave Length | Dominant Wave Length | Viewing Angle 2 θ ½ | Forward Voltage @20mA (V) | | Luminous Intensity @20mA (mcd) | |
|--|----------------|---------------|------------------|----------------------|-------------------------------|------------------------------|-----|-----------------------------------|------|
| | | | nm | nm | Deg | Typ | Max | Min | Typ |
| PL321-1Y01 | Yellow | GaAsP | 585 | 590 | 34° | 2.1 | 2.6 | 15.0 | 35.0 |

All dimensions are in **Millimeters**. Tolerance is $\pm 0.25\text{mm}$ unless otherwise specified.

