

Applied Motion Products, Inc. 404 Westridge Dr. Watsonville, CA 95076, USA 1-800-525-1609 Tel (831) 761-6555 Fax (831) 761-6544

Product Datasheet

www.Applied-Motion.com

STAC6-Si-220

AC Advanced Microstep Drive w/ Si Programming & Encoder Input

1pc. - 1,205.00 50pc. - 903.75



Product Features

- 100 lines of icon based program capability
- Si is heralded for its programming ease
- Animation mode displays operation in real time, great for debugging
- 15 digital inputs, 7digital outputs, all optically isolated
- Optional MMI-01 for menu selection, flow control and inputting parameters
- Capable of all "Q" and "S" drive control modes
- RS-232 cable and all mating connectors are included



Description

The STAC6-Si-220 stepper drive is a powerful, two-phase, bipolar step motor drive for high-speed, high-torque applications. It employs sophisticated current control designed for optimal smoothness over a wide speed range. Anti-resonance, torque ripple smoothing, and microstepping work together to bring step motor performance to a new high.

The STAC6-Si-220 operates on single-phase 220 VAC and outputs up to 3.2 A/phase (peak-of-sine) to the step motor. It features over-voltage, over-temperature, and over-current protection and is complemented by a specially matched set of low-loss NEMA 23 and NEMA 34 frame step motors.

The STAC6-Si-220 can operate in all of the same control modes as a Q drive, plus it has the ability to run standalone Si programs stored in non-volatile memory. Si programs are created using the <u>Si Programmer™</u> software, which provides unparalleled simplicity in indexer-drive programming via Applied Motion's unique and powerful iconbased programming environment.

For connecting to external devices such as limit switches, proximity or photoelectric sensors, PLC I/O, lamps, and other devices, the STAC6-Si-220 stepper drive comes with 15 digital inputs and 7 digital outputs. *Note: 2 single-ended analog inputs, which can be wired together as 1 differential analog input, are also available, but not in Si program mode.*


The STAC6-Si-220 stepper drive comes with an RS-232 port for configuration and programming. It also provides an RS-485 port for streaming serial (SCL) and Q commands in single-axis applications when used in the SCL or Q Program control modes.


Each STAC6 drive comes with an encoder feedback connector for applications that demand a higher level of position control than ordinary open-loop step motor systems can provide. Use our double-shaft step motors with incremental encoders and activate either Stall Detection or Stall Prevention in the drive. Stall Detection notifies the system as soon as the required torque is too great for the motor, which results in a loss of synchronization between the rotor and stator, also known as stalling. Stall Prevention automatically adjusts motor speed to maintain synchronization of the rotor to the stator under all conditions. This unique feature allows step motors to operate in a much broader range of applications than previously possible, such as torque-control. The Stall Prevention feature also performs static position maintenance, which maintains the position of the motor shaft when at rest. Additionally, the inclusion of the optional encoder allows the motor to be precisely homed to the index (marker) pulse.

The STAC6-Si-220 is CE approved and RoHS compliant.

Model Number:	STAC6-Si-220				
Part Number:	5000-123				
Supply Voltage:	94-264 VAC				
Supply Voltage Type:	AC				
Control Modes:	Si Programming				
Output Current:	0.5-3.2 A/phase				
Communication Ports:	RS-232 RS-485				
Encoder Feedback:	Yes				
Step Resolution:	Full				
	Half Microstepping Microstep Emulation				
Idle Current Reduction:					
Setup Method:	Software setup				
Digital Inputs:	: 15				
Digital Outputs:	7				
Analog Inputs:	1 differential or 2 single-ended				
Dimensions:	6.35 x 4.66 x 2.31 inches				
Weight:	36 oz				
Operating Temperature Range:	0-55 °C				
Ambient Temperature Range:	0-55 °C				
Ambient Humidity:	90% max, non-condensing				
Status LEDs:	1 red, 1 green				
Circuit Protection:	Short circuit Over-voltage Under-voltage Over-temp				

Torque Curves





Software

Software:

DSP Firmware Downloader Si Firmware Downloader Si Programmer™


Downloads

Manuals:	✓ STAC6_Hardware_Manual_920-0029.pdf ✓ STAC6_QuickSetup_920-0060.pdf			
Datasheet:	http://s3.amazonaws.com/applied-motion-pdf/STAC6-Si-220.pdf			
Family Datasheet:	STAC6_Datasheet_925-0012.pdf			
2D Drawing:	d <u>STAC6_Three_Views.pdf</u> d <u>STAC6_simple3D.pdf</u>			
3D Drawing:	STAC6_Simple.igs			
Speed-Torque Curves:	STAC6_speed-torque.pdf			
Agency Approvals:	d STAC6_EMC_CE_DOC.pdf d STAC6_LVD_CE_DOC.pdf			
Application Notes:	APPN0016_Simple-25-pin-mating-connections.pdf APPN0015_Make-a-serial-programming-cable.pdf			

Pricing

	STAC6-Si-220 Part No. 5000-123			
1pc.	\$1,205.00			
25pc.	\$1,036.30			
50pc.	\$903.75			
100pc.	Request a Quote for 100+ piece pricing.			

2D Drawings



Products in the Series STAC6 Stepper Drives

r 🗘	Supply Voltage	Control Modes 🗘	Output Current	Communication Ports	Encoder Feedback	1pc./50pc. 🗘
<u>AC6-C</u>	94-135 VAC	CANopen	0.5-6.0 A/Phase	RS-232, CANopen	Yes	\$1107.00 / \$830.25
<u>)6-C-220</u>	94-265 VAC	CANopen	0.5-3.2 A/Phase	RS-232, CANopen	Yes	\$1212.00 / \$909.00
AC6-Q	94-135 VAC	Streaming Commands, Analog Positioning, Encoder Following, Q Programming	0.5-6.0 A/Phase	RS-232, RS-485	Yes	\$1005.00 / \$753.75
06-Q-220	94-265 VAC	Streaming Commands, Analog Positioning, Encoder Following, Q Programming	0.5-3.2 A/Phase	RS-232, RS-485	Yes	\$1140.00 / \$855.00
<u>.C6-QE</u>	94-135 VAC	Streaming Commands, Analog Positioning, Encoder Following, Q Programming	0.5-6.0 A/Phase	RS-232, RS-485	Yes	\$1160.00 / \$870.00
6-QE-220	94-265 VAC	Streaming Commands, Analog Positioning, Encoder Following, Q Programming	0.5-3.2 A/Phase	RS-232, RS-485	Yes	\$1305.00 / \$978.75
<u>AC6-S</u>	94-135 VAC	Step & Direction, Velocity (Oscillator), Streaming Commands, SiNet Hub Compatible	0.5-6.0 A/Phase	RS-232, RS-485	Yes	\$820.00 / \$615.00
6-S-220	94-265 VAC	Step & Direction, Velocity (Oscillator), Streaming Commands, SiNet Hub Compatible	0.5-3.2 A/Phase	RS-232, RS-485	Yes	\$973.00 / \$729.75
AC6-Si	94-135 VAC	Si Programming	0.5-6.0 A/Phase	RS-232, RS-485	Yes	\$1077.00 / \$807.75
<u>6-Si-220</u>	94-264 VAC	Si Programming	0.5-3.2 A/Phase	RS-232, RS-485	Yes	\$1205.00 / \$903.75