



ROITHNER LASERTECHNIK

Wiedner Hauptstraße 76, A-1040 Vienna, Austria

Tel.: ++43 1 586 52 43-0, Fax -44, office@roithner-laser.com



RLTMRL-685 / 5~20mW

RED DIODE LASER At 685nm

Diode red laser 685nm is made features of ultra compact, long lifetime, low cost and easy operating, which is widely used in measurement, spectrum analysis, laser lighting show, etc.



SPECIFICATIONS

Wavelength (nm)	685 ± 5		
Output power (mW)	> 5, 10, 15, 20		
Transverse mode	Near TEM ₀₀		
Operating mode	CW		
Power stability (rms, over 4 hours)	<1%, <3%, <5%		
Warm-up time (minutes)	<5		
M ² factor	<20		
Beam divergence, full angle (mrad)	<0.5		
Dimensions of beam at the aperture (mm)	~4.0		
Beam height from base plate (mm)	24.8		
Polarization ratio	>50:1		
Pointing stability after warm-up (mrad)	<0.05		
Operating temperature (°C)	10~35		
Power supply (90-264VAC or 5VDC)	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
TTL / Analog modulation	Optional, 2kHz or higher (on request, up to 30kHz)		
Expected lifetime (hours)	10000		
Warranty	1 year		



MxL-III-685	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
140. 8(L)×73(W)×46. 2(H) mm³, 0.6kg	154 (L) ×155(W) ×95 (H) mm³, 1.5kg	133 (L) ×130(W) ×65 (H) mm³, 1.2kg	100 (L) ×60(W) ×56 (H) mm³, 0.2kg