


# Si PIN photodiodes



S2506 series

S6775 series

S6967

## Plastic SIP (single in-line package)

S2506/S6775 series and S6967 are Si PIN photodiodes with large active areas, molded into a clear or visible-cut plastic SIP for detecting visible to near infrared range or near infrared range only. These Si PIN photodiodes feature a high sensitivity, a high-speed response and large active areas.

### Features

- **S2506-02: Visible to near infrared range**  
**S2506-04: Visible-cut**  
**S6775, S6967: Visible to near infrared range, high sensitivity, high-speed response, large active area**
- **S6775-01: Visible-cut, high sensitivity, high-speed response, large active area**
- **Plastic package: 7 × 7.8 mm**
- **Photosensitive area size**  
**S2506 series: 2.77 × 2.77 mm**  
**S6775 series, S6967: 5.5 × 4.8 mm**

### Applications

- **FSO (free space optics)**
- **Optical switches**
- **Laser radar, etc.**

### General ratings / Absolute maximum ratings

Type no.	Package	Photosensitive area size (mm)	Effective photosensitive area (mm <sup>2</sup> )	Absolute maximum ratings			
				Reverse voltage V <sub>R</sub> max. (V)	Power dissipation P (mW)	Operating temperature T <sub>opr</sub> (°C)	Storage temperature T <sub>stg</sub> (°C)
S2506-02	Plastic	2.77 × 2.77	7.7	35	150	-25 to +85	-40 to +100
S2506-04					50		
S6775		5.5 × 4.8	26.4		50		
S6775-01							
S6967							

Note: Exceeding the absolute maximum ratings even momentarily may cause a drop in product quality. Always be sure to use the product within the absolute maximum ratings.

### Electrical and optical characteristics (Typ. T<sub>a</sub>=25 °C, unless otherwise noted)


Type no.	Spectral response range λ (nm)	Peak sensitivity wavelength λ <sub>p</sub> (nm)	Photosensitivity S (A/W)				Short circuit current I <sub>sc</sub> 100 lx (μA)	Dark current I <sub>D</sub>		Temp. coefficient of I <sub>D</sub> T <sub>CI<sub>D</sub></sub> (times/°C)	Cut-off frequency f <sub>c</sub> R <sub>L</sub> =50 Ω -3 dB (MHz)	Terminal capacitance C <sub>t</sub> f=1 MHz (pF)	NEP (W/Hz <sup>1/2</sup> )	
			λ <sub>p</sub>	660 nm	780 nm	830 nm		Typ. (nA)	Max. (nA)					
S2506-02	320 to 1100	960	0.56	0.4	0.48	0.5	7.3	0.1*1	10*1	1.15	25*1	15*1	1.0 × 10 <sup>-14*1</sup>	
S2506-04	760 to 1100			-	-	0.25	4.1							
S6775	320 to 1100	960	0.7	0.45	0.55	0.6	30	0.5*2	10*2		15*2	40*2		1.8 × 10 <sup>-14*2</sup>
S6775-01	700 to 1100			0.68	-	0.48	0.54							21
S6967	320 to 1060			0.65	0.45	0.55	0.6				26	5*2		50*2

\*1: V<sub>R</sub>=12 V


\*2: V<sub>R</sub>=10 V

**Spectral response**


S2506 series




S6775 series, S6967




**Photo sensitivity temperature characteristic (S2506-02)**




**Dark current vs. reverse voltage**



**Dark current vs. ambient temperature**




**Terminal capacitance vs. reverse voltage**




**Directivity**

S2506-02





Relative sensitivity

S6775/-01, S6967



Relative sensitivity

**Dimensional outline (unit: mm, tolerance unless otherwise noted: ±0.1)**



Type no.	A	B
S2506 series	2.8 ± 0.2	2.77 × 2.77
S6775/series S6967	3.65 ± 0.2	5.5 × 4.8

Lead surface finish: Silver plating  
 Packing: Polyethylene pack [anti-static type]  
 (200 pcs/pack)

KPINA0084ED

**Related information**

[www.hamamatsu.com/sp/ssd/doc\\_en.html](http://www.hamamatsu.com/sp/ssd/doc_en.html)

## ■ Precautions

- Notice
- Metal, ceramic, plastic package products

## ■ Technical information

- Si photodiode/Application circuit examples

Information described in this material is current as of November, 2014.

Product specifications are subject to change without prior notice due to improvements or other reasons. This document has been carefully prepared and the information contained is believed to be accurate. In rare cases, however, there may be inaccuracies such as text errors. Before using these products, always contact us for the delivery specification sheet to check the latest specifications.

The product warranty is valid for one year after delivery and is limited to product repair or replacement for defects discovered and reported to us within that one year period. However, even if within the warranty period we accept absolutely no liability for any loss caused by natural disasters or improper product use.

Copying or reprinting the contents described in this material in whole or in part is prohibited without our prior permission.

**HAMAMATSU**[www.hamamatsu.com](http://www.hamamatsu.com)

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, Bridgewater, N.J. 08807, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 8152-375-0, Fax: (49) 8152-265-8

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Torshamnsgatan 35 16440 Kista, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.r.l.: Strada della Moia, 1 int. 6, 20020 Arese (Milano), Italy, Telephone: (39) 02-93581733, Fax: (39) 02-93581741

China: Hamamatsu Photonics (China) Co., Ltd.: B1201, Jiaming Center, No.27 Dongsanhuan Beilu, Chaoyang District, Beijing 100020, China, Telephone: (86) 10-6586-6006, Fax: (86) 10-6586-2866