

H.QL5~300KV/3.0A Product Data

High voltage rectifier block adopts high reliable mesa structure and diffusion craftwork, epoxy resin molded in a compact structure.

■ Feature

- Avalanche characteristic
- More sizes to choose
- Epoxy resin molded in vacuum, have anticorrosion in the surface
- Operating Junction Temperature Tj: -40°C—+150°C

■ Application

- High voltage rectifier used in electrostatic cleaning
- High voltage generator
- High voltage testing equipment
- General purpose high voltage rectifier, voltage multiplier assembly


■ Limiting Value (Absolute Maximum Rating)

Item	Symbol	Unit	Conditions	Data
Repetitive Peak Reverse Voltage (Single Arm)	V_{RRM}	KV	Ta=25°C I _R =1.0μA	5~300.0
Peak Working Reverse Voltage (Single Arm)	V_{RWM}	KV	Ta=25°C I _R =1.0μA	5~300.0
Non-Repetitive Peak Reverse Voltage (Single Arm)	V_{RSM}	KV	Ta=25°C I _R =1.0μA	6~360.0
Average Forward Current	I _{F(AV)}	A	(50KHz Half-sine Wave , Resistance load @T _{break} =50°C)	3.0
Reverse Recovery Time	trr	nS	I _F =50mA I _R =100mA I _{RR} =25mA	--
Surge Forward Current	I _{FSM}	A	0.01S @ Half-Sine wave 50Hz	200.0
Operating Ambient Temperature	T _a	°C		-40~+125
Storage Temperature	T _{stg}	°C		-40~+125


■ Electrical Characteristic (Ta=25°C Unless Otherwise Specified)

Forward Peak Voltage (Single Arm; Reference Value)	V_{FM}	V	@ Ta=25°C I _F =0.02A	6.0~360.0
Peak Reverse Current (Reference Value)	I _{RRM1}	μA	@ Ta=25°C V _{RM} =V _{RRM}	5.0
	I _{RRM2}	μA	@ Ta=100°C V _{RM} =V _{RRM}	100.0


■ Characteristic Curve



Forward Characteristics



Reverse Characteristics



Avalanche Breakdown Voltage Distribution