

isc Triacs


BTA10-600B

FEATURES

- With TO-220AB insulated package
- Suitable for general purpose AC switching. Which can be used as an ON/OFF function in applications such as static relays, heating regulation, induction motor starting circuits. Or for phase control operation in light dimmers, motor speed controllers etc.

ABSOLUTE MAXIMUM RATINGS(Ta=25°C)

SYMBOL	PARAMETER	MIN	UNIT
V_{DRM}	Repetitive peak off-state voltage	600	V
V_{RRM}	Repetitive peak reverse voltage	600	V
$I_{T(RMS)}$	RMS on-state current (full sine wave) $T_j=105^\circ\text{C}$	10	A
I_{TSM}	Non-repetitive peak on-state current $t_p=20\text{ms}$	100	A
T_j	Operating junction temperature	110	°C
T_{stg}	Storage temperature	-45~150	°C
$R_{th(j-c)}$	Thermal resistance, junction to case	2.4	°C/W
$R_{th(j-a)}$	Thermal resistance, junction to ambient	60	°C/W

ELECTRICAL CHARACTERISTICS ($T_c=25^\circ\text{C}$ unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MAX	UNIT	
I_{RRM}	Repetitive peak reverse current	$V_R=V_{RRM}$, $V_R=V_{RRM}$, $T_j=110^\circ\text{C}$	0.01 0.5	mA	
I_{DRM}	Repetitive peak off-state current	$V_D=V_{DRM}$, $V_D=V_{DRM}$, $T_j=110^\circ\text{C}$	0.01 0.5	mA	
I_{GT}	Gate trigger current	$V_D=12\text{V}$; $R_L=30\ \Omega$	I	50	mA
			II	50	
			III	50	
			IV	100	
I_H	Holding current	$I_{GT}=0.1\text{A}$, Gate Open	50	mA	
V_{GT}	Gate trigger voltage all quadrant	$V_D=12\text{V}$; $R_L=30\ \Omega$	1.3	V	
V_{TM}	On-state voltage	$I_T=14\text{A}$; $t_p=380\ \mu\text{s}$	1.55	V	