


FCS-1152 2MP 2MP: 1




! Mounting kits are to be ordered separately.

Fixed Network Camera, 5-Megapixel, 802.3af PoE, 2MP/2MP, WDR



1. Ethernet Port
2. Memory Card Slot
3. Power LED
4. Reset Button
5. Audio Input/ Output & Digital Input/ Output



6. Monitor Distance Adjustment
7. Focal Length Adjustment
8. DC Iris Port

Key Features

- 2MP 2MP Micro SDHC/SDXC 2MP
- 5-Megapixel (2592 x 1944) 2MP
- 2MP 2MP 2MP 2MP WDR(2MP 2MP) 2MP
- 2MP: H.264/MJPEG
- 2MP 2MP 2MP 2MP IR-2 2MP
- Power support: PoE (IEEE 802.3af)
- 2MP 64-bit 2MP 2MP 2MP(OneSecure App 2MP)



System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet

IEEE 802.3u 100-BASE-TX, Fast Ethernet

IEEE 802.3af Power over Ethernet (PoE)

TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour

Image Sensor:

5-Megapixel 1/3.2" Progressive Scan CMOS

Connectors and Cabling:

1 x RJ-45 10/100 Mbps PoE Port

1 x Auto Iris (DC Drive)

I/O terminal block (1 DI/1 DO)

Modularity:

1 x MicroSDHC/ MicroSDXC card slot

Button:

Reset Button

Indicator:

Power

Lens:

Vari-focal, DC iris, Manual focus, f2.8-12mm, F1.4

IR Cut Filter:

Removable infrared-cut filter for day & night function

Shutter Time:

1/5 ~ 1/10,000 sec

Angle of View:

70.9° - 29.2°

Pan/Tilt/Zoom:

Digital Zoom to very high detail available on Software

Video Compression:

H.264 / MJPEG

Resolution:

5M (2592x1944)

Video Format:

RAW

Audio Compression:

G.711

Power:

Power Consumption: PoE Class 2 (IEEE802.3af) / 4.002W

Power Input: 802.3af PoE

Features

General:

Backup: MicroSDHC /MicroSDXC card slot for local storage

Video:

Image Setting: - Adjustable image size, quality and bit rate

- Configurable brightness, sharpness, contrast, saturation, white balance and exposure

- AGC/AWB/AES

- Back Light Compensation (BLC)

- Wide Dynamic Range (WDR), Basic WDR (74 dB)

- 2D Noise Reduction (2DNR)

Streaming: Up to 2 video streams

Performance

Data Transfer Rate:

10/100Mbps

Storage Capacity:

SD/MicroSD memory card of up to 64GB

Frame Rate:

15fps at 2592 x 1944; 15 fps at 2048x1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 720; 30 fps at 640 x 480; 15 fps at 320 x 240

Minimum illumination:

Color: 0.1 lux at F1.4

B/W: 0.05 lux at F1.4

Environment

Temperature (°C):

Operating: -10°C ~ 50°C

Humidity (Non-condensing):

Operating: 10% ~ 85%

Physical Specifications

Dimensions (W x D x H mm):

67 x 169 x 65 mm

Weight (g):

438 g

Others

Approval and Compliance:


CE, FCC, ONVIF

Deployment:

Wall Mount

Operation Systems:

Microsoft Windows 8/7/Vista/XP





Order Information

FCS-1152

Package Contents

FCS-1152

Screw Kit

Quick Installation Guide

Resource CD (User Manual, QIG)



CAS-3104

Bracket for Indoor Box Cameras

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.