

LED Module Specifications

PRODUCT SPECIFICATION

Model No.: FYLM-5050UXX-01-11-12V-W

Applications:
<ul style="list-style-type: none"> ■ Channel Letters ■ Lighting source for shop windows ■ Indoor Decoration Lighting ■ Advertising Signs ■ Replacement for Neon



CUSTOMER APPROVED SIGNATURES	APPROVED BY	CHECKED BY	PREPARED BY

NINGBO FORYARD OPTOELECTRONICS CO.,LTD.

Add: NO.115 Qixin Road Ningbo Zhejiang China

Zip: 315042

Tel: 0086-574-87933652 87927870 87922206


Fax: 0086-574-87927917

E-mail: Sales@foryard.com (General)

[Http://www.foryard.com](http://www.foryard.com)

Model No.: FYLM-5050UXX-01-11-12V-W


■ Photo



■ Features

1. Adopt 5050 SMD LED, long lifetime, low attenuation, high efficacy
2. Cascade up to 50 pcs
3. Molding with lens, uniform light, waterproof, dustproof, anti-UV
4. Product is compliant with CE, RoHS and Bureau of Quality Supervision report

■ Profile Drawings



Notes:

1. All dimensions are millimeters.
2. Tolerance is $\pm 1\text{mm}$ unless otherwise specified.
3. Specifications are subject to change without notice.

Model No.: FYLM-5050UXX-01-11-12V-W

Rating Electrical/Optical Characteristics(1 PCS)

Item	Cold White	Red
Color Temperature(K)	9000	620~625
Wavelength(nm)		
Luminous Flux(lm/piece)	20	6.5
CRI	≥75	-
Luminous Efficiency(lm/W)	83.3	27
Working Voltage (V)	DC12	
Beam Angle (°)	150	
Working Current	20	
Power(W/piece)	0.24	
net weight:(g)	5.25	
LED Quantity(pcs)	1	
Dimension:(mm)	26.75*16.4	
Life Time(hrs)	13000	
Operation Temperature(°C)	-25~+60	
IP Grade	IP 66	
Approval	CE (NO: E8 06 01 57489 001)	

Rating Electrical/Optical Characteristics(50 PCS)

LED Color	Cold White	Red
Power Dissipation	12W	
Total Length	5.14m±0.1m	
Input Current(mA)	1000	
Weight	262.5g	



Notes:

1. Testing environment temperature: 25±2°C
2. The above data are typical values; the actual data of each single product could differ from the typical value. The data subject to change without prior notice.


Model No.: FYLM-5050UXX-01-11-12V-W

Package(5 meters)

The backsides of all products will stick '3M' branded double-sided sticker with 10mm width.





XPCS/Polybag



24Boxes/Carton

OUTSIDE LABEL



xPolybags/Box



OUTSIDE LABEL

Note: The specifications are subject to change without notice. Please contact us for updated information.