

Vectron International**Filter specification****TFS 261B****1/5****Measurement condition**

Ambient temperature:	23	°C
Input power level:	0	dBm
Terminating impedance: *		
Input:	720 Ω	-5,7 pF
Output:	580 Ω	-6,7 pF

Characteristics

Remark:

The reference level for the relative attenuation a_{rel} of the TFS 261B is the minimum of the pass band attenuation a_{min} . The minimum of the pass band attenuation a_{min} is defined as the insertion loss a_e . The centre frequency f_c is the arithmetic mean value of the upper and lower frequencies at the 1,5 dB filter attenuation level relative to the insertion loss a_e . The nominal frequency f_N is fixed at 261,0 MHz without any tolerance. The given values for both the relative attenuation a_{rel} and the group delay ripple have to be achieved at the frequencies given below even if the centre frequency f_c is shifted due to the temperature coefficient of frequency TC_f in the operating temperature range and due to a production tolerance for the centre frequency f_c .

D a t a		typ. value	tolerance / limit
Insertion loss (reference level)	a_e	6,8 dB	max. 11,0 dB
Nominal frequency	f_N	-	261,0 MHz
Centre frequency	f_c	261,0 MHz	-
Pass band	PB	-	$f_N \pm 150,0$ kHz
Pass band ripple		-	max. 1,0 dB
Pass band variation		0,75 dB	max. 1,5 dB
Relative attenuation	a_{rel}		
$f_N \pm 150,0$ kHz		0,75 dB	max. 1,5 dB
$f_N - 260,0$ MHz ... $f_N - 0,8$ MHz		43 dB	min. 40 dB
$f_N + 0,8$ MHz ... $f_N + 239,0$ MHz		43 dB	min. 40 dB
Group delay	at $f_N @ 25^\circ\text{C}$	1,58 μs	max. ±100 ns
Group delay ripple within PB		105 ns	max. 200 ns
Pulse response**** (drive pulse Trapezoidal pulse 3.5μs width, 10-90% rise & fall time = 2.0+/-0.25μs)			min. 35 dB
Subsequent sidelobes, (after the main lobe)		38 dB	min. 16 dB
Third echo, (third sidelobe after the main lobe)		58 dB	min. 35 dB
Return loss within $f_N \pm 100$kHz		-	min. 15 dB
Input power level	**	-	max. 20 dBm
Operable temperature range		-	- 40 °C ... + 105 °C
Operating temperature range	OTR	-	- 40 °C ... + 85 °C
Storage temperature range		-	- 62 °C ... + 105 °C
Frequency inversion temperature		22 °C	-
Temperature coefficient of frequency	TC_f ***	-0,04 ppm/K ²	-

*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.

***) for short term operation only, cycle time 1:1000; 15 dBm max for continuous operation



****) $\Delta f(\text{Hz}) = TC_f(\text{ppm/K}^2) \times (T - T_0)^2 \times f_{cat}(\text{MHz})$.

*****) The pulse response performance has been simulated using measured device s-parameters and the final performance is an inherent feature of the design.

Generated:**Checked / Approved:****Vectron International GmbH & Co. KG****Potsdamer Straße 18****D 14 513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30****E-Mail: ift@vectron.com**


Vectron International GmbH & Co. KG reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Filter characteristic



Construction and pin connection


(All dimensions in mm)



- 1 Input
- 2 Ground
- 3 Ground
- 4 Ground
- 5 Output RF Return
- 6 Output
- 7 Ground
- 8 Ground
- 9 Ground
- 10 Input RF Return

Date code: Year + week
 X 2009
 A 2010
 B 2011
 ...

50 Ω Test circuit



Vectron International GmbH & Co. KG
 Potsdamer Straße 18
 D 14 513 TELTOW / Germany
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
 E-Mail: tft@vectron.com

Vectron International GmbH & Co. KG reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Stability characteristics, reliability

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 1 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: three times max.;
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;
5. ESD ANSI/ESD S20.20-1999, class 1A for HBM


This filter is RoHS compliant (2002/95/EG, 2005/618/EG)

Packing

- Tape & Reel: IEC 286 – 3, with exception of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;
- | | |
|---|-------------|
| max. pieces of filters per reel: | 1500 |
| reel of empty components at start: | min. 300 mm |
| reel of empty components at start including leader: | min. 500 mm |
| trailer: | min. 300 mm |


Tape (all dimensions in mm)

- W : 24,00
- Po : 4,00
- Do : 1,50
- E : 1,75
- F : 11,50
- G(min) : 0,60
- P2 : 2,00
- P1 : 12,00
- D1(min) : 1,50
- Ao : 8,80
- Bo : 14,60
- Ct : 21,5



Reel (all dimensions in mm)

- A : 330
- W1 : 24,4
- W2(max) : 30,4
- N(min) : 60
- C : 13,0



The minimum bending radius is 45 mm.


Vectron International GmbH & Co. KG
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@vectron.com

Vectron International GmbH & Co. KG reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

Conditions	Exposure
Average ramp-up rate (30°C to 217°C)	less than 3°C/second
> 100°C	between 300 and 600 seconds
> 150°C	between 240 and 500 seconds
> 217°C	between 30 and 150 seconds
Peak temperature	max. 260°C
Time within 5°C of actual peak temperature	between 10 and 30 seconds
Cool-down rate (Peak to 50°C)	less than 6°C/second
Time from 30°C to Peak temperature	no greater than 300 seconds

Chip-mount air reflow profile



Vectron International GmbH & Co. KG
 Potsdamer Straße 18
 D 14 513 TELTOW / Germany
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
 E-Mail: tft@vectron.com

Vectron International GmbH & Co. KG reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

History

Version	Reason of Changes	Name	Date
1.0	Generation of development specification	Strehl	20.01.2009
1.1	- add of terminating impedances, typical values, filter characteristics and matching configuration - change of time domain parameters	Pfeiffer	19.05.2009