

TPSMA6L Series




Maximum Ratings and Thermal Characteristics
($T_A=25^{\circ}\text{C}$ unless otherwise noted)

| Parameter | Symbol | Value | Unit |
|--|-----------------|------------|----------------------|
| Peak Pulse Power Dissipation at $T_A=25^{\circ}\text{C}$ by 10x1000 μs Waveform (Fig.2)(Note 1), (Note 2) | P_{PPM} | 600 | W |
| Power Dissipation on Infinite Heat Sink at $T_A=50^{\circ}\text{C}$ | $P_{M(AV)}$ | 3 | W |
| Peak Forward Surge Current, 8.3ms Single Half Sine Wave (Note 3) | I_{FSM} | 60 | A |
| Maximum Instantaneous Forward Voltage at 25A for Unidirectional Only | V_F | 3.5V | V |
| Operating Junction and Storage Temperature Range | T_J, T_{STG} | -65 to 150 | $^{\circ}\text{C}$ |
| Typical Thermal Resistance Junction to Lead | $R_{\theta JL}$ | 35 | $^{\circ}\text{C/W}$ |
| Typical Thermal Resistance Junction to Ambient | $R_{\theta JA}$ | 200 | $^{\circ}\text{C/W}$ |

Notes:

1. Non-repetitive current pulse, per Fig.4 and derated above $T_A=25^{\circ}\text{C}$ per Fig. 3.
2. Mounted on 5.0x5.0mm copper pad to each terminal.
3. Measured on 8.3ms single half sine wave or equivalent square wave for unidirectional device only.

Functional Diagram



Description

The TPSMA6L Series is designed specifically to protect sensitive electronic equipment from voltage transients induced by load dump and other transient voltage events, and it's especially suitable for high reliability and automotive applications.

SMA low profile package (DO221-AC) has the same electrical performance as the SMB package but with low height profiles (1.1mm).

Features

- Hi reliability application and automotive grade AEC-Q101 qualified
- SMA low profile package: less than 1.1 mm
- Same power as standard SMB devices (600 W)
- Footprint compatibility with standard SMA and SMB products (easy to lay out)
- Typical failure mode is short from over-specified voltage or current
- Whisker test is conducted based on JEDEC JESD201A per its table 4a and 4c
- IEC-61000-4-2 ESD 15kV(Air), 8kV (Contact)
- ESD protection of data lines in accordance with IEC 61000-4-2 (IEC801-2)
- EFT protection of data lines in accordance with IEC 61000-4-4 (IEC801-4)
- Low inductance, excellent clamping capability
- Fast response time: typically less than 1.0ns from 0 Volts to $V_{BR\ min}$
- Built-in strain relief
- Glass passivated junction
- Typical I_r less than 1 μA above 12V
- High temperature soldering: 260 $^{\circ}\text{C}/40$ seconds at terminals
- Typical maximum temperature coefficient $\Delta V_{BR} = 0.1\% \times V_{BR} @ 25^{\circ}\text{C} \times \Delta T$
- Matte tin lead-free plated
- Halogen free and RoHS compliant


Applications

TVS devices are ideal for the protection of I/O Interfaces, V_{CC} bus and other vulnerable circuits used in Telecom, Computer, Industrial and Consumer electronic applications.

Electrical Characteristics ($T_c=25^\circ\text{C}$ unless otherwise noted)

| Part Number (Uni) | Marking | Reverse Stand-off Voltage V_R (Volts) | Breakdown Voltage V_{BR} (Volts) @ I_T | | Test Current I_T (mA) | Maximum Clamping Voltage V_C @ I_{PP} (V) | Maximum Peak Pulse Current I_{PP} (A) | Maximum Reverse Leakage I_R @ V_R (μA) |
|-------------------|---------|---|--|--------|-------------------------|---|---|---|
| | | | MIN | MAX | | | | |
| TPSMA6L5.0A | AEA | 5.0 | 6.40 | 7.00 | 10 | 9.2 | 65.3 | 800 |
| TPSMA6L6.0A | AGA | 6.0 | 6.67 | 7.37 | 10 | 10.3 | 58.3 | 800 |
| TPSMA6L6.5A | AKA | 6.5 | 7.22 | 7.98 | 10 | 11.2 | 53.6 | 500 |
| TPSMA6L7.0A | AMA | 7.0 | 7.78 | 8.60 | 10 | 12.0 | 50.0 | 200 |
| TPSMA6L7.5A | APA | 7.5 | 8.33 | 9.21 | 1 | 12.9 | 46.6 | 100 |
| TPSMA6L8.0A | ARA | 8.0 | 8.89 | 9.83 | 1 | 13.6 | 44.2 | 50 |
| TPSMA6L8.5A | ATA | 8.5 | 9.44 | 10.40 | 1 | 14.4 | 41.7 | 20 |
| TPSMA6L9.0A | AVA | 9.0 | 10.00 | 11.10 | 1 | 15.4 | 39.0 | 10 |
| TPSMA6L10A | AXA | 10.0 | 11.10 | 12.30 | 1 | 17.0 | 35.3 | 5 |
| TPSMA6L11A | AZA | 11.0 | 12.20 | 13.50 | 1 | 18.2 | 33.0 | 1 |
| TPSMA6L12A | BEA | 12.0 | 13.30 | 14.70 | 1 | 19.9 | 30.2 | 1 |
| TPSMA6L13A | BGA | 13.0 | 14.40 | 15.90 | 1 | 21.5 | 28.0 | 1 |
| TPSMA6L14A | BKA | 14.0 | 15.60 | 17.20 | 1 | 23.2 | 25.9 | 1 |
| TPSMA6L15A | BMA | 15.0 | 16.70 | 18.50 | 1 | 24.4 | 24.6 | 1 |
| TPSMA6L16A | BPA | 16.0 | 17.80 | 19.70 | 1 | 26.0 | 23.1 | 1 |
| TPSMA6L17A | BRA | 17.0 | 18.90 | 20.90 | 1 | 27.6 | 21.8 | 1 |
| TPSMA6L18A | BTA | 18.0 | 20.00 | 22.10 | 1 | 29.2 | 20.6 | 1 |
| TPSMA6L20A | BVA | 20.0 | 22.20 | 24.50 | 1 | 32.4 | 18.6 | 1 |
| TPSMA6L22A | BXA | 22.0 | 24.40 | 26.90 | 1 | 35.5 | 16.9 | 1 |
| TPSMA6L24A | BZA | 24.0 | 26.70 | 29.50 | 1 | 38.9 | 15.5 | 1 |
| TPSMA6L26A | CEA | 26.0 | 28.90 | 31.90 | 1 | 42.1 | 14.3 | 1 |
| TPSMA6L28A | CGA | 28.0 | 31.10 | 34.40 | 1 | 45.4 | 13.3 | 1 |
| TPSMA6L30A | CKA | 30.0 | 33.30 | 36.80 | 1 | 48.4 | 12.4 | 1 |
| TPSMA6L33A | CMA | 33.0 | 36.70 | 40.60 | 1 | 53.3 | 11.3 | 1 |
| TPSMA6L36A | CPA | 36.0 | 40.00 | 44.20 | 1 | 58.1 | 10.4 | 1 |
| TPSMA6L40A | CRA | 40.0 | 44.40 | 49.10 | 1 | 64.5 | 9.3 | 1 |
| TPSMA6L43A | CTA | 43.0 | 47.80 | 52.80 | 1 | 69.4 | 8.7 | 1 |
| TPSMA6L45A | CVA | 45.0 | 50.00 | 55.30 | 1 | 72.7 | 8.3 | 1 |
| TPSMA6L48A | CXA | 48.0 | 53.30 | 58.90 | 1 | 77.4 | 7.8 | 1 |
| TPSMA6L51A | CZA | 51.0 | 56.70 | 62.70 | 1 | 82.4 | 7.3 | 1 |
| TPSMA6L54A | REA | 54.0 | 60.00 | 66.30 | 1 | 87.1 | 6.9 | 1 |
| TPSMA6L58A | RGA | 58.0 | 64.40 | 71.20 | 1 | 93.6 | 6.5 | 1 |
| TPSMA6L60A | RKA | 60.0 | 66.70 | 73.70 | 1 | 96.8 | 6.2 | 1 |
| TPSMA6L64A | RMA | 64.0 | 71.10 | 78.60 | 1 | 103.0 | 5.9 | 1 |
| TPSMA6L70A | RPA | 70.0 | 77.80 | 86.00 | 1 | 113.0 | 5.3 | 1 |
| TPSMA6L75A | RRA | 75.0 | 83.30 | 92.10 | 1 | 121.0 | 5.0 | 1 |
| TPSMA6L78A | RTA | 78.0 | 86.70 | 95.80 | 1 | 126.0 | 4.8 | 1 |
| TPSMA6L85A | RVA | 85.0 | 94.40 | 104.00 | 1 | 137.0 | 4.4 | 1 |

I-V Curve Characteristics



- P_{PPM} Peak Pulse Power Dissipation** – Max power dissipation
- V_R Stand-off Voltage** – Maximum voltage that can be applied to the TVS without operation
- V_{BR} Breakdown Voltage** – Maximum current that flows through the TVS at a specified test current (I_T)
- V_C Clamping Voltage** – Peak voltage measured across the suppressor at a specified I_{ppm} (peak impulse current)
- I_R Reverse Leakage Current** – Current measured at V_R
- V_F Forward Voltage Drop for Uni-directional**

Ratings and Characteristic Curves ($T_A=25^\circ\text{C}$ unless otherwise noted)

Figure 1 - TVS Transients Clamping Waveform





Figure 2 - Peak Pulse Power Rating Curve



continues on next page.

Ratings and Characteristic Curves ($T_A=25^\circ\text{C}$ unless otherwise noted) (Continued)

Figure 3 - Pulse Derating Curve




Figure 4 - Pulse Waveform




Figure 5 - Typical Junction Capacitance






Figure 6 - Steady State Power Dissipation Derating Curve



Soldering Parameters

| | | |
|--|------------------------------------|-------------------------|
| Reflow Condition | | Lead-free assembly |
| Pre Heat | - Temperature Min ($T_{s(min)}$) | 150°C |
| | - Temperature Max ($T_{s(max)}$) | 200°C |
| | - Time (min to max) (t_s) | 60 – 180 secs |
| Average ramp up rate (Liquidus Temp (T_L) to peak) | | 3°C/second max |
| $T_{s(max)}$ to T_L - Ramp-up Rate | | 3°C/second max |
| Reflow | - Temperature (T_L) (Liquidus) | 217°C |
| | - Time (min to max) (t_s) | 60 – 150 seconds |
| Peak Temperature (T_p) | | 260 ^{+0/-5} °C |
| Time within 5°C of actual peak Temperature (t_p) | | 20 – 40 seconds |
| Ramp-down Rate | | 6°C/second max |
| Time 25°C to peak Temperature (T_p) | | 8 minutes max. |
| Do not exceed | | 280°C |





Physical Specifications

| | |
|-----------------|--|
| Weight | 0.002 ounce, 0.061 gram |
| Case | JEDEC DO-221AC molded plastic over glass passivated junction |
| Polarity | Color band denotes cathode except bipolar |
| Terminal | Matte tin-plated leads, solderable per JESD22-B102D |

Environmental Specifications

| | |
|---------------------------|-------------|
| Temperature Cycle | JESD22-A104 |
| Pressure Cooker | JESD22-A102 |
| High Temp. Storage | JESD22-A103 |
| HTRB | JESD22-A108 |
| Thermal Shock | JESD22-A106 |


Dimensions




Mounting Pad Layout

| Dimensions | Inches | | Millimeters | |
|------------|--------|-------|-------------|-------|
| | Min | Max | Min | Max |
| A | 0.156 | 0.181 | 3.950 | 4.600 |
| B | 0.189 | 0.220 | 4.800 | 5.600 |
| C | 0.049 | 0.069 | 1.250 | 1.750 |
| D | 0.088 | 0.116 | 2.250 | 2.950 |
| E | 0.030 | 0.059 | 0.750 | 1.500 |
| F | 0.005 | 0.010 | 0.125 | 0.250 |
| G | 0.035 | 0.043 | 0.900 | 1.100 |

Part Numbering System



Part Marking System



Packaging

| Part number | Component Package | Quantity | Packaging Option | Packaging Specification |
|-------------|-------------------|----------|----------------------------|-------------------------|
| TPSMA6LxxA | DO-221AC | 3000 | Tape & Reel – 12mm/7" tape | EIA RS-481 |

Tape and Reel Specification

