



Elastische Einpresszone mit Übergabesteckzone / compliant pressfit zone with mating transfer zone  
 Isolierwerkstoff / housing material : PBT GF30  
 Bauart 7 / type 7  
 Anforderungsstufe 2 = 400 Steckzyklen / performance class 2 = 400 mating cycles  
 Fehlende Masse und Angaben nach IEC 60 603-2 / DIN EN 60 603-2  
 Missing information and dimensions per IEC 60 603-2 / DIN EN 60 603-2  
 Schichtaufbau im metallisierten Loch siehe Zeichnung 164062 / Nr.6  
 diameter of drilled hole see drawing 164062 / No.6

1)  $\varnothing 1,0 \pm 0,09$  Durchmesser des metallisierten Loches  
 $\varnothing 1,0 \pm 0,09$  Diameter of finished plated-through hole  
 $\varnothing 1,15 \pm 0,025$  Bohrungsdurchmesser des Loches  
 $\varnothing 1,15 \pm 0,025$  Diameter of drilled hole

Information:	Tolerances	 All Dimensions in mm	Scale	2:1
	All rights reserved. Only for information. To insure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Designation <b>Federleiste B/2, 32 EE</b> <b>Fem. Connector B/2, Pressfit</b>	
Subject to modification without prior notice. Drawing will not be updated.		 www.ERNI.com	<b>284319</b>	
Index	Date	V:00062557.SZA	STVB/2	

Consider protection memo from DIN 34