



VRLA Rechargeable Battery

EP7-12



FEATURES

- Absorbent Glass Mat technology for efficient gas recombination
- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Can be used in any orientation(excluding used inverted)
- The battery is designed for heavy duty cyclic application
- Low self-discharge rate, lower than 3% capacity loss per month

APPLICATION

- UPS
- Toy-Cars
- Power Packs
- Fishing Lights
- Laboratory Equipment



SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	7.0Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	2600g(5.73lbs.)
Terminals	T2(Faston Tab 250) T1 is optional
Internal Resistance	≤25mΩ (Fully Charged)
Max. Discharge Current	105 A (5 sec.)
Max. Charge Current	2.1 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	Standard: ABS(UL 94-HB) EP7-12 Optional: Flame Retardant ABS(UL 94-V0) EP7-12FR

ISO9001 **UL** MH19884

ISO14001 **CE** CAM20310-2474-E-16

OHSMS

- IEC 61056-1
- JIS C 8702-1
- GB/T 19639.1

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<p>■ Length 151±1.5 (5.94±0.06)</p> <p>■ Width 65±1.5 (2.56±0.06)</p> <p>■ Container Height 93±1.5 (3.66±0.06)</p> <p>■ Total Height 98±2.0 (3.86±0.08)</p>		<p>● Terminal T1</p> <p>● Terminal T2</p>

Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell)	Discharge Time	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V		228.0	171.4	138.8	83.50	48.40	20.40	14.10	7.86	4.11
1.75V		264.0	185.7	145.3	86.70	49.80	20.80	14.30	7.98	4.20
1.70V		280.0	192.4	149.7	88.60	50.70	21.00	14.40	8.02	4.22
1.65V		293.0	197.0	153.2	89.90	51.40	21.20	14.50	8.04	4.23
1.60V		302.0	200.9	156.2	90.80	51.90	21.30	14.50	8.04	4.23

Constant current discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell)	Discharge Time	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V		20.54	15.09	12.07	7.076	4.067	1.700	1.175	0.655	0.343
1.75V		24.22	16.35	12.63	7.347	4.185	1.733	1.192	0.665	0.350
1.70V		25.69	16.94	13.02	7.508	4.261	1.750	1.200	0.668	0.352
1.65V		26.88	17.34	13.32	7.619	4.319	1.767	1.208	0.670	0.353
1.60V		27.71	17.68	13.58	7.695	4.361	1.775	1.208	0.670	0.353

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.