

# LFP1300-A5NMC

LFP Cubic

**LEVEL SENSORS** 





### Ordering information

Туре	Part no.
LFP1300-A5NMC	1062256

Other models and accessories → www.sick.com/LFP\_Cubic

Illustration may differ



#### Detailed technical data

#### **Features**

Medium	Fluids
Measurement	Switch, Continuous
Design	Standard
Probe type	Mono rod probe
Probe length	1,300 mm
Process pressure	-1 bar 10 bar
Process temperature	-20 °C +100 °C
GOST approval	<b>✓</b>
RoHS certificate	<b>✓</b>
IO-Link	<b>✓</b>
CULus certificate	✓

#### Performance

Accuracy of sensor element	± 5 mm <sup>1)</sup>
Repeatability	≤ 2 mm
Resolution	< 2 mm
Response time	< 400 ms
Dielectricity constant	≥ 5 for mono rod probe / rope probe ≥ 1.8 with coaxial tube
Conductivity	No limitation
Maximum level change	≤ 500 mm/s
Deactivated area at end of probe	10 mm <sup>1)</sup>

 $<sup>^{1)}</sup>$  With water under reference conditions.

# LFP1300-A5NMC | LFP Cubic

LEVEL SENSORS

MTTF

194.3 years (EN ISO 13849-1)

#### Electronics

 $<sup>^{1)}</sup>$  With water under reference conditions.

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

## **WORLDWIDE PRESENCE:**

Contacts and other locations <u>-www.sick.com</u>

