Rev	AWO #	Description	Date	Appr
-		RELEASED	01/17/07	

APPROVED: _____

DATE: _____ TITLE: _____





PCB LAYOUT





SPECIFICATIONS:
Material:
Insulator: Hi-temp thermoplastic, rated UL 94V-0
Insulator color: Ivory
Contacts: Brass
Plating:
Tin over Nickel underplate overall
Electrical:
Operating voltage: 100 VAC max
Current rating: 1 Amps max
Contact resistance: 20 mohms max
Insulation resistance: 500 Mohms min
Dielectric withstanding voltage: 500 VAC for 1 minute
Temperature Rating:
Operating temperature: -25°C to +85°C
Environmental:
Lead free, RoHS compliant.

RoHS COMPLIANT

A=.049 [1.25] X NO. OF SPACES
B=.049 [1.25] X NO. OF SPACES +.098 [2.50]

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	BW	01/17/07
CHECKED		
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE 1.25mm WAFER, DIP R/A

SIZE	PART NO.	REV.
X	125SH-C-XX-TR	-

REF: | SCALE: NTS | SHEET 1 OF 1