CMLT8099

SURFACE MOUNT SILICON DUAL NPN TRANSISTOR



APPLICATIONS:

· Small signal general purpose amplifiers

Central semiconductor corp.

www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMLT8099 consists of two individual, isolated 8099 NPN silicon transistors, manufactured by the epitaxial planar process and epoxy molded in an SOT-563 surface mount package. This device has been designed for small signal general purpose amplifier applications.

MARKING CODE: C89

FEATURES:

- Device is Halogen Free by design
- Current I_C=500mA
- Voltage V_{CEO}=80V

MAXIMUM RATINGS: (TA=25°C)	SYMBOL		UNITS
Collector-Base Voltage	V_{CBO}	80	V
Collector-Emitter Voltage	V_{CEO}	80	V
Emitter-Base Voltage	V_{EBO}	6.0	V
Continous Collector Current	$I_{\mathbb{C}}$	500	mA
Power Dissipation	P_{D}	350	mW
Operating and Storage Junction Temperature	T _J , T _{stg}	-65 to +150	°C
Thermal Resistance	Θ_{JA}	357	°C/W

ELECTRICAL CHARACTERISTICS PER TRANSISTOR: (T_A=25°C unless otherwise noted)


SYMBOL	TEST CONDITIONS	MÍN	MAX	UNITS
I _{CBO}	V _{CB} =80V		0.1	μΑ
I _{EBO}	V _{BE} =6.0V		0.1	μΑ
BV_{CBO}	I _C =100μA	80		V
BV _{CEO}	I _C =10mA	80		V
BV_{EBO}	I _E =10μA	6.0		V
V _{CE(SAT)}	I _C =100mA, I _B =5.0mA		0.4	V
V _{CE} (SAT)	I _C =100mA, I _B =10mA		0.3	V
V _{BE(ON)}	V _{CE} =5.0V, I _C =10mA	0.6	8.0	V
h _{FE}	V _{CE} =5.0V, I _C =1.0mA	100	300	
h _{FE}	V _{CE} =5.0V, I _C =10mA	100		
h _{FE}	V _{CE} =5.0V, I _C =100mA	75		
f_{T}	V _{CE} =5.0V, I _C =10mA, f=100MHz	150		MHz
C_{ob}	V _{CB} =10V, I _E =0, f=1.0MHz		6.0	pF
C _{ib}	V_{BE} =0.5V, I_{C} =0, f=1.0MHz		25	pF


CMLT8099

SURFACE MOUNT SILICON DUAL NPN TRANSISTOR




SOT-563 CASE - MECHANICAL OUTLINE





PIN CONFIGURATION



DIMENSIONS							
	INCHES		MILLIMETERS				
SYMBOL	MIN	MAX	MIN	MAX			
Α	0.0027	0.007	0.07	0.18			
В	0.008		0.20				
С	0.017	0.024	0.45	0.60			
D	0.059	0.067	1.50	1.70			
E	0.020		0.50				
F	0.059	0.067	1.50	1.70			
G	0.043	0.051	1.10	1.30			
Н	0.006	0.012	0.15	0.30			
SOT-563 (REV: R2)							

LEAD CODE:

- 1) Emitter Q1
- 2) Base Q1
- 3) Collector Q2
- 4) Emitter Q2
- 5) Base Q2
- 6) Collector Q1

MARKING CODE: C89

R3 (29-June 2015)

CMLT8099





SERVICES

- · Bonded Inventory
- Custom Electrical Screening
- Custom Electrical Characteristic Curves
- SPICE Models
- Custom Packaging
- Package Base Options
- Custom Device Development/Multi Discrete Modules (MDM™)
- · Bare Die Available for Hybrid Applications

LIMITATIONS AND DAMAGES DISCLAIMER: In no event shall Central be liable for any collateral, indirect, punitive, incidental, consequential, or exemplary damages in connection with or arising out of a purchase order or contract or the use of products provided hereunder, regardless of whether Central has been advised of the possibility of such damages. Excluded damages shall include, but not be restricted to: cost of removal or reinstallation, rework, ancillary costs to the procurement of substitute products, loss of profits, loss of savings, loss of use, loss of data, or business interruption. No claim, suit, or action shall be brought against Central more than two (2) years after the related cause of action has occurred.

In no event shall Central's aggregate liability from any warranty, indemnity, or other obligation arising out of or in connection with a purchase order or contract, or any use of any Central product provided hereunder, exceed the total amount paid to Central for the specific products sold under a purchase order or contract with respect to which losses or damages are claimed. The existence of more than one (1) claim against the specific products sold to Buyer under a purchase order or contract shall not enlarge or extend this limit.

Buyer understands and agrees that the foregoing liability limitations are essential elements of a purchase order or contract and that in the absence of such limitations, the material and economic terms of the purchase order or contract would be substantially different.

R3 (29-June 2015)