

D-subminiature parallel and serial cables

Ready-to-use cabling – call for custom lengths!**Features**

- Fully molded backshell with strain relief for added protection
- 26 AWG stranded conductors for flexibility
- Thumbscrews for tool-less termination
- All wired straight through except as noted

DB25 to DB25 – All pins terminated

| Male to Female | Male to Male | Length | 1-9 | 10-19 | 20-49 | 50-99 | 100+ |
|----------------|--------------|---------------|-----|-------|-------|-------|------|
| 232AMF5 | 232AMM5 | 1.8 m (6 ft) | | | | | |
| 232AMF1 | 232AMM1 | 3.0 m (10 ft) | | | | | |
| 232AMF15 | — | 4.6 m (15 ft) | | | | | |
| — | 232AMM2 | 7.9 m (26 ft) | | | | | |
| 232AMF2 | — | 7.9 m (26 ft) | | | | | |

DB9 to DB9 – All pins terminated

| Male to Female | Male to Male | Length | 1-9 | 10-19 | 20-49 | 50-99 | 100+ |
|----------------|--------------|---------------|-----|-------|-------|-------|------|
| 9PAMF6 | 9PAMM6 | 1.8 m (6 ft) | | | | | |
| 9PAMF10 | 9PAMM10 | 3.0 m (10 ft) | | | | | |
| 9PAMF15 | — | 4.6 m (15 ft) | | | | | |
| 9PAMF25 | 9PAMM25 | 7.9 m (26 ft) | | | | | |

DB9 to DB25 adapter cable – 15.2 cm (6 in) cable converts 25-pin serial port to a 9-pin AT serial port

| DB9 Male to DB25 Female | DB9 Female to DB25 Male | 1-9 | 10-19 | 20-49 | 50-99 | 100+ |
|-------------------------|-------------------------|-----|-------|-------|-------|------|
| 232CAMR | 232CAMS | | | | | |

DB9 female to DB25 male modem cable – 9-wire, all pins terminated– PC-AT modem Cable

| DB25 Male to DB9 Female | Length | 1-9 | 10-19 | 20-49 | 50-99 | 100+ |
|-------------------------|---------------|-----|-------|-------|-------|------|
| 232CAM | 1.8 m (6 ft) | | | | | |
| 232CAM10 | 3.0 m (10 ft) | | | | | |

9-pin null modem cable – Pins 2 and 3 crossed for RS-232 compliance – DB9 connectors on both ends

| Female to Female | Male to Female | Length | 1-9 | 10-19 | 20-49 | 50-99 | 100+ |
|------------------|----------------|---------------|-----|-------|-------|-------|------|
| 232NM9FF6 | 232NM9MF6 | 1.8 m (6 ft) | | | | | |
| 232NM9 | 232NM9MF10 | 3.0 m (10 ft) | | | | | |
| 232NM9FF25 | 232NM9MF25 | 7.9 m (26 ft) | | | | | |

Port saver – Protect a highly used port from mechanical damage – Saves you from replacing an expensive card due to port damage

| Model No. | Description | 1-9 | 10-19 | 20-49 | 50-99 | 100+ |
|-----------|--------------------------------|-----|-------|-------|-------|------|
| 9PSMF | Male to female DB9 port saver | | | | | |
| 232PSMF | Male to female DB25 port saver | | | | | |

USB Cables**High performance USB connectivity and USB extension****Features – USB cables**

- Connect your PC or device to any cable-less USB peripheral
- Type A male to Type B male
- Fully rated USB 2.0 peripheral cables

Features – USB extension cable

- This 3 meter extension cable extends a short cable on a USB peripheral to the full 5 meters length allowed (total cable length must not exceed 5 meters)
- Type A male to type A female



| Model No. | Length | 1-9 | 10-19 | 20-49 | 50-99 | 100+ |
|-------------|------------|-----|-------|-------|-------|------|
| USBAMBM-3F | 3 ft (1m) | | | | | |
| USBAMBM-6F | 6 ft (2m) | | | | | |
| USBAMBM-15F | 15 ft (5m) | | | | | |

| Model No. | Length | 1-9 | 10-19 | 20-49 | 50-99 | 100+ |
|-------------|------------|-----|-------|-------|-------|------|
| USBAMAF-10F | 10 ft (3m) | | | | | |