

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|----|-----|-----------------|-----------|-----|------|
| A | | INITIAL RELEASE | 16DEC2014 | DW | CW |
| B | | ECR-15-013750 | 19SEP2015 | DW | CW |
| B1 | | ECR-15-016224 | 05NOV2015 | DW | CW |
| B2 | | ECR-16-017507 | 12DEC2016 | QY | CW |

M3 SCREW, RECOMMENDED
TIGHTENING TORQUE 0.5Nm
M3 螺丝, 推荐锁紧力矩0.5Nm

TYPE-1, T2010032101-000, TE LOGO
类型-1, T2010032101-000, TE LOGO

SEAL / 密封圈

31.4

NOTES:

1. TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 250 V
RATED CURRENT: 10 A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 4 KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
WIRE RANGE: 0.5-2.5 mm² (20-14 AWG)
CONTACT FINISH: SILVER PLATED
CONTACT TYPE: SCREW CONTACT

注释:

1. 技术参数:
绝缘材料: PC
额定电压: 250V
额定电流: 10A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 4 KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500 次
接线范围: 0.5-2.5 mm² (20-14 AWG)
端子表面处理: 镀银
接线类型: 螺丝连接

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

| | |
|--------|----|
| 0 PLC | ±- |
| 1 PLC | ±- |
| 2 PLC | ±- |
| 3 PLC | ±- |
| 4 PLC | ±- |
| ANGLES | ±- |

MATERIAL

-

FINISH

-

DWN 16DEC2014

DAVID WANG

CHK 16DEC2014

CHRIS WANG

APVD 16DEC2014

XU XIANG

PRODUCT SPEC

108-137045

APPLICATION SPEC

114-137045

WEIGHT

-

Customer Drawing

TE Connectivity

NAME

HA-003-M

SIZE

A3

CAGE CODE

00779

DRAWING NO

G-T2010032101000

RESTRICTED TO

-

SCALE

2:1

SHEET

1 OF 2

REV B2

1470-19 (3/13)

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|---|-----|-------------|------|-----|------|
| - | | SEE SHEET 1 | - | - | - |
| | | | | | |
| | | | | | |

NOTE:
SEE SHEET 1

注释:
见页 1

ALL DIMENSIONS ARE SAME AS TYPE 1,
EXCEPT THOSE DEFINED IN THIS TYPE.
除了在本类型中定义的尺寸外, 其它尺寸同类型 1

TYPE-2, T2010032101-001, NO LOGO
类型-2, T2010032101-001, 无 LOGO

| | | | |
|-------------------|------------------------|--|----------------|
| T2010032101-001 | HA-003-M | HA-003 MALE INSERT, NO LOGO HA-003公插, 无LOGO | TYPE-2 类型-2 |
| T2010032101-000 | HA-003-M | HA-003 MALE INSERT HA-003公插 | TYPE-1 类型-1 |
| PART NUMBER 料号 | PART DESCRIPTION 描述 | | TYPE 类型 |

| | | | | |
|--|--|--------------------------------|---|--|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN 16DEC2014 DAVID WANG | | |
| DIMENSIONS: mm | | CHK 16DEC2014 CHRIS WANG | | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: | | APVD 16DEC2014 XU XIANG | NAME HA-003-M | |
| 0 PLC ±- | | PRODUCT SPEC 108-137045 | SIZE CAGE CODE DRAWING NO RESTRICTED TO | |
| 1 PLC ±- | | APPLICATION SPEC 114-137045 | A300779 C-T2010032101000 - | |
| 2 PLC ±- | | WEIGHT - | SCALE 2:1 SHEET 2 OF 2 REV B2 | |
| 3 PLC ±- | | Customer Drawing | | |
| 4 PLC ±- | | | | |
| ANGLES ±- | | | | |
| FINISH - | | | | |
| MATERIAL - | | | | |

1470-19 (3/13)