



7/16 DIN Male to 7/16 DIN Male Low PIM Cable 168 Inch Length Using 1/2 inch Flexible Coax, RoHS

TECHNICAL DATA SHEET

PE39802-168

1/2" Flexible Coax Low PIM Assembly

High Performance Factory Assembled Corrugated Coaxial Cable Jumpers

- Soldering Technology and connector design provides a very durable assembly with superior PIM and VSWR performance.
- Carefully selected assemblies provide the highest quality available on the market today.
- 100% electrical tested for PIM and VSWR ensuring optimum installed performance.
- Available in 1/2" Flexible and 1/2" Superflexible cables in any length, offering the best cable solution for the required performance and application.
- Injection molded boot for added strain relief and weather sealing ensuring long term durability.
- PE39802 1/2" Flexible cable assemblies are available in standard lengths of 36, 48, 72, 96, 120, 144, 168, 192, and 240 inches. Custom lengths available on request.

Configuration

Connector 1	7/16 DIN Male
Connector 2	7/16 DIN Male
Cable Type	1/2" Flexible

Electrical Specifications

Frequency Range, GHz	DC to 2.7
Impedance, Ohms	50
Maximum VSWR	1.11:1
Velocity of Propagation, %	88
RF Shielding, dB	120
Peak Power, KWatts	40
Passive Intermodulation, dBc	-160

Typical Performance by Frequency

Frequency 1

Frequency, MHz	900
VSWR	1.07:1
Insertion Loss	0.02 dB/ft + 0.1 dB [0.07 dB/m + 0.1 dB]

Frequency 2

Frequency, GHz	1.8
VSWR	1.09:1
Insertion Loss	0.03 dB/ft + 0.1 [0.1 dB/m + 0.1 dB]

Frequency 3

Frequency, GHz	2.2
VSWR	1.09:1
Insertion Loss	0.034 dB/ft + 0.1 dB [0.11 dB/m + 0.1 dB]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male to 7/16 DIN Male Low PIM Cable 168 Inch Length Using 1/2 inch Flexible Coax, RoHS PE39802-168](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.





7/16 DIN Male to 7/16 DIN Male Low PIM Cable 168 Inch Length Using 1/2 inch Flexible Coax, RoHS

TECHNICAL DATA SHEET

PE39802-168

Frequency 4

Frequency, GHz	2.7
VSWR	1.11:1
Insertion Loss	0.04 dB/ft + 0.1 dB [0.13 dB/m + 0.1 dB]

Mechanical Specifications

Cable Assembly

Cable Type	1/2" Flexible
------------	---------------

Temperature

Temperature Operating Range, deg C	-40 to +80
------------------------------------	------------

Size

Length, in [cm]	168 [426.72]
Diameter, in [mm]	0.629 [15.98]
Weight, lbs [g]	0.155 [70.31]
Cable Color	Black
One Time Minimum Bend Radius, in [mm]	2.75 [69.85]
Repeated Minimum Bend Radius, in [mm]	4.72 [119.89]

Cable

Center Conductor Type	Solid
Cable Inner Conductor	Copper Clad Aluminum
No of Shields	1
Dielectric Type	PE (F)
Jacket Material	PE
Jacket Diameter, in [mm]	0.629 [15.98]

Connector 1

Type	7/16 DIN Male
Configuration	Straight
Inner Conductor Material and Plating	Brass, Silver
Outer Conductor Material and Plating	Brass, Silver
Coupling Nut Material and Plating	Brass, Tri-Metal
Hex Size, mm	32
Torque, ft-lbs [Nm]	18.417 [24.97]
Body Material and Plating	Brass, Silver
Dielectric Type	PTFE

Connector 2

Type	7/16 DIN Male
Configuration	Straight
Inner Conductor Material and Plating	Brass, Silver
Outer Conductor Material and Plating	Brass, Silver

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male to 7/16 DIN Male Low PIM Cable 168 Inch Length Using 1/2 inch Flexible Coax, RoHS PE39802-168](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



7/16 DIN Male to 7/16 DIN Male Low PIM Cable 168 Inch Length Using 1/2 inch Flexible Coax, RoHS

TECHNICAL DATA SHEET

PE39802-168

Coupling Nut Material and Plating	Brass, Tri-Metal
Hex Size, mm	32
Torque, ft-lbs [Nm]	18.417 [24.97]
Body Material and Plating	Brass, Silver
Dielectric Type	PTFE

Compliance Certifications (visit www.Pasternack.com for current document)
RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

7/16 DIN Male to 7/16 DIN Male Low PIM Cable 168 Inch Length Using 1/2 inch Flexible Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male to 7/16 DIN Male Low PIM Cable 168 Inch Length Using 1/2 inch Flexible Coax, RoHS PE39802-168](http://www.pasternack.com/7-16-male-7-16-male-1-2-flexible-cable-pe39802-168-p.aspx)

URL: <http://www.pasternack.com/7-16-male-7-16-male-1-2-flexible-cable-pe39802-168-p.aspx>


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE39802-168 CAD Drawing

7/16 DIN Male to 7/16 DIN Male Low PIM Cable 168 Inch

Length Using 1/2 inch Flexible Coax, RoHS



Part # Ext.	Length In Inches	Part # Ext.	Length In Centimeters
-36	36"	-	-
-48	48"	-	-
-72	72"	-	-
-96	96"	-	-
-120	120"	-	-
-XX	Custom Length	-XXCM	Custom Length

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES (mm).
 4. LENGTH TOLERANCE IS ± 1.5% OR 3/8", WHICHEVER IS GREATER.

How To Order

Part Number Configuration

PE3 [zzz] [yy] - [xx] [uu]

00 - 99999

LF = Lead Free
< Blank > = Standard

Note: LF applies only to RF cables

Examples

PE3000LF-100


PE3000-100

PE3000LF-100CM

PE3000-100CM

CM = Centimeters
< Blank > = Inches

Length



PASTERNAK ENTERPRISES
ESTABLISHED 1972

PASTERNAK ENTERPRISES, INC.
 P.O. BOX 16759, IRVINE, CA 92623
 PHONE (949) 261-1920 FAX (949) 261-7451
 WEB ADDRESS: www.pasternack.com
 E-MAIL ADDRESS: sales@pasternack.com
COAXIAL & FIBER OPTICS

REV. -

FSCM NO. 53919

CAD FILE 041612

SCALE N/A

SIZE A

2233