


ACT751T-4 , ACT751VT-4 Clipped Sine Wave TCXO/VCTCXO

- Stability: ± 1.5 ppm
- VCXO $\pm 5, \pm 10$ ppm tuning
- Aging ± 1.0 ppm



Characteristics

Frequency Range (MHz)	12 ~ 26
Supply voltage $\pm 5\%$ Vcc (V _{DC})	3.3 to 5.0
Operating temperature Top (°C)	Table 1
Operating Current (mA max)	2.0
Stability v T op (ppm)	Table 1
Stability v Vcc(ppm)	± 0.3 (5%)
Stability v Load (ppm)	± 0.3 (10%)
Aging @25°C (ppm)	± 1.0 /yr
Load $\pm 10\%$	CSW: 10K Ω /10pF
Output voltage (V)	0.8 p-p max (3.3V), 1.0 p-p max (5V)
Start up time (ms, max)	2.5 max 2.0 typ

VCTCXO only

Slope / Linearity	Positive / 10%
Control voltage (V _{DC})	1.65 \pm 1.65 to 2.5 \pm 2.5
Frequency Tuning (ppm)	$\pm 5, \pm 10$

Rating

Storage temperature (°C)	-40~+85
--------------------------	---------

Notes:

ESD sensitive, take appropriate precautions.







Table 1 Temperature °C	Stability (ppm)								
	± 1.0	± 1.5	± 2.0	± 2.5	± 3.0	± 3.5	± 4.0	± 4.5	± 5.0
0~50	✓	✓	✓	✓	✓	✓	✓	✓	✓
-10~60		✓	✓	✓	✓	✓	✓	✓	✓
-10~70		✓	✓	✓	✓	✓	✓	✓	✓
-20~70			✓	✓	✓	✓	✓	✓	✓
-30~70				✓	✓	✓	✓	✓	✓
-30~75				✓	✓	✓	✓	✓	✓
-40~80				✓	✓	✓	✓	✓	✓
-40~85				✓	✓	✓	✓	✓	✓



Tape & Reel Dimensions (mm)



To specify: Please refer to part numbering system appended to the end of this data

ISO9001 Registered

For quotations or further information please contact us at:
 3 The Business Centre, Molly Millars Lane, Wokingham, Berkshire, RG41 2EY
 Issue No. 5 Skr Date: 07/10/2013

ACT751T-4 , ACT751VT-4 Clipped Sine Wave TCXO/VCTCXO

TCXO PART NUMBERING

VT78	2700	F	B	D	N	B	X	X		Z	C	-PF
751T	27.00MHz	±5 ppm	3.3 V _{DC}	0 +50 °C	None	CSW	None	Pos	Not spec	%	1000	RoHS

751T	VT78
------	------

Stability v T _{OP} ±ppm	
5.0	F
4.0	J
3.5	K
3.0	L
2.5	M
2.0	N
1.5	O
1.0	P

T _{OP} °C	
0 +50	D
-10 +60	F
-10 +70	C
-20 +70	B
-30 +70	T
-30 +75	W
-40 +80	K
-40 +85	I

Polarity	
None	X

Commodity Code
854370 70 99

 Standard

V _{CC} V _{DC}	
3.3	B
5	A
Free	O
A voltage within the range must be specified.	

Frequency tuning	
None	N

Duty Cycle % / %	
Not specified	Z

Output CSW	
CSW	B

Mechanical Tuning ±ppm	
None	X

Tape & Reel	
1000	C
Loose	L

Frequency:
 Please enquire if the frequency/stability combination has been developed.
 For part numbering use the first 4 characters of the frequency in Hz i.e. 27MHz = 27000000Hz so the code used in the part number is 2700. If the frequency is 100MHz or higher then the first 5 characters are used.
 It is important to suffix the part number

Example

VT78 - 2700FBDNBXXZC-PF 27.00MHz

Temperature °C	Stability (ppm)								
	±1.0	±1.5	±2.0	±2.5	±3.0	±3.5	±4.0	±4.5	±5.0
0-50	✓	✓	✓	✓	✓	✓	✓	✓	✓
-10-60		✓	✓	✓	✓	✓	✓	✓	✓
-10-70			✓	✓	✓	✓	✓	✓	✓
-20-70				✓	✓	✓	✓	✓	✓
-30-70					✓	✓	✓	✓	✓
-30-75						✓	✓	✓	✓
-40-80							✓	✓	✓
-40-85								✓	✓

ISO9001 Registered

For quotations or further information please contact us at:
 3 The Business Centre, Molly Millars Lane, Wokingham, Berkshire, RG41 2EY
 Issue No. 5 Skr Date: 07/10/2013

ACT751T-4 , ACT751VT-4 Clipped Sine Wave TCXO/VCTCXO

VCTCXO PART NUMBERING

T78	2700	F	B	D	E	B	X	D	P	E	Z	C	-PF
751VT	27.00MHz	±5 ppm	3.3 V _{DC}	0 +50 °C	cntl only	csw	None	± ppm	Pos	± %	specified %	1000	RoHS

751VT	T78
-------	-----

Stability V T _{OP} ±ppm	
5.0	F
4.0	J
3.5	K
3.0	L
2.5	M
2.0	N
1.5	O
1.0	P

T _{OP} °C	
0 +50	D
-10 +60	F
-10 +70	C
-20 +70	B
-30 +70	T
-30 +75	W
-40 +80	K
-40 +85	I

Electrical Tuning ±ppm	
5	D
10	F

Commodity Code
854370 70 99

 Standard

Polarity	
Positive	P

V _{CC} V _{DC}	
3.3	B
5	A
Free	O
A voltage within the range must be specified.	

Frequency tuning	
V cntl only	E

Linearity ±%	
10	E

Output CSW	
	B

Duty Cycle % / %	
Not specified	Z

Frequency:
 Please enquire if the frequency/stability combination has been developed.
 For part numbering use the first 4 characters of the frequency in Hz i.e. 27MHz = 27000000Hz so the code used in the part number is 2700. If the frequency is 100MHz or higher then the first 5 characters are used.
 It is important to suffix the part number

Tape & Reel	
1000	C
Loose	L

Mechanical Tuning ±ppm	
None	X

Example

T78 - 2700FBDEBXDPEZC-PF 27.00MHz

Temperature °C	Stability (ppm)								
	±1.0	±1.5	±2.0	±2.5	±3.0	±3.5	±4.0	±4.5	±5.0
0-50	✓	✓	✓	✓	✓	✓	✓	✓	✓
-10-60		✓	✓	✓	✓	✓	✓	✓	✓
-10-70		✓	✓	✓	✓	✓	✓	✓	✓
-20-70			✓	✓	✓	✓	✓	✓	✓
-30-70				✓	✓	✓	✓	✓	✓
-30-75					✓	✓	✓	✓	✓
-40-80						✓	✓	✓	✓
-40-85							✓	✓	✓