
KEMET Part Number: MPCH1250L1R5

(UPIC1250L1R500)



Power, MPCH, 1500 nH, 20%



General Information	
Style:	SMD Chip
Series:	MPCH
Description:	Shielded, Surface Mount Inductor
Features:	Large Current Inductors
RoHS:	Yes
Core:	Composite

Dimensions	
Chip Size	5649
L	14.3mm MAX
W	12.5mm +/-0.3mm
Т	5mm MAX
LL	2.2mm NOM
G	2.5mm NOM

Specifications	
Inductance:	1.5 uH (0.1 MHz)
Inductance Tolerance:	20%
Temperature Range:	-20/+120C
Shielded:	Yes
Current:	21000 mAmps (Isat, 20% Drop In Inductance), 21000 mAmps (Irms, 40C Rise By Self Heating)
DC Resistance:	2.2 mOhms

Packaging Specifications	
Packaging:	T&R, 380mm
Packaging Quantity:	500

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

