

Specification

Part No.	FXP07.B.07.0100A
Product Name	Embedded 2G/3G Flex Monopole Antenna
Features	Very low profile Penta band GSM Adhesive tape for easy mounting 100mm ø1.13 cable IPEX MHFI(U.FL comp) connector Dims:41*24mm RoHS compliant



1. Introduction

FXP07B.07.0100A is a general version of stick-on flexible PCB. It is designed with 100mm 1.13mm coaxial cable and the IPEX connector for easy installation. FXP07B.07.0100A is ideal for small compact applications such as POS (Point of Sale) devices. It can be soldered to the edge of the main device ground-plane to optimize the efficiency.

Antenna Specification 2.

PENTA-BAND CELLULAR							
Band (MHz)	824~894	880~960	1710~1880	1850~1990	2110~2170		
Efficiency (%)	> 30%	> 40%	> 40%	> 40%	> 40%		
Peak Gain (dBi)	> 0	> 1	> 1	> 1	> 1		
Impedance	50 Ohm						
Radiation Pattern	Omni-directional						
Polarization	Linear						
FPCB	41x24mm						
Connector	IPEX MHFI (U.FL comp)						
Cable	ø1.13 cable						
Cable Length	100mm						
Adhesive Tape	3M 467						
Operation Temperature(°C)	-40°C~+85°C						
Storage Temperature (°C)	-40°C~+85°C						

^{*} All measurements are done in free space with standard cables


^{*} The ABS housing size 125x45x2mm

^{*} The Ground plane size 106x45x1mm



3. Antenna Characteristics


3.1. Return Loss



SPE-11-8-063/D/SS | page 3 of 19




3.2. Peak Gain vs. Frequency



SPE-11-8-063/D/SS | page 4 of 19




3.3. Efficiency vs. Frequency






3.4. XYZ Co-ordinate for Reference



3.5. Radiation pattern


3.5.1. XY Plane @ 825MHz




SPE-11-8-063/D/SS | page 6 of 19



3.5.2. YZ Plane @ 825MHz




3.5.3. XZ Plane @ 825MHz






3.5.4.XY Plane @ 880MHz




3.5.5. YZ Plane @ 880MHz






3.5.6.XZ Plane @ 880MHz




3.5.7.XY Plane @ 960MHz






3.5.8. YZ Plane @ 960MHz




3.5.9.XZ Plane @ 960MHz






3.5.10. XY Plane @ 1710MHz




3.5.11. YZ Plane @ 1710MHz






3.5.12. XZ Plane @ 1710MHz




3.5.13. XY Plane @ 1880MHz






3.5.14. YZ Plane @ 1880MHz




3.5.15. XZ Plane @ 1880MHz






3.5.16. XY Plane @ 1990MHz




3.5.17. YZ Plane @ 1990MHz






3.5.18. XZ Plane @ 1990MHz




3.5.19. XY Plane @ 2170MHz






3.5.20. YZ Plane @ 2170MHz




3.5.21. XZ Plane @ 2170MHz






4. Mechanical Drawing






5. Installation

1: Adhesive Mount on Plastic



2: Solder Mount on PCB Footprint





6. Packaging

