



## PL00193 Series Bi-Color SMD LED 1204 Package

### Features

- \*Dome lens thin package 3.2 x 1.0 x 1.5mm
- \*Low current requirements
- \*High light output
- \*Compatible with IR solder-process
- \*Industry standard footprint
- \*4000 pcs per reel
- \*RoHS compliant

### Absolute Maximum Ratings at T<sub>A</sub> = 25°C

Power Dissipation.....	78mW
Reverse Voltage (<10μA) .....	5.0V
Max Forward Current .....	30mA
Peak Forward Current(1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range .....	-40°C to +85°C
Storage Temperature Range .....	-40°C to +85°C
Reflow Soldering Temperature.....	260°C for 10 seconds

### Electrical & Optical Characteristics at T<sub>A</sub> = 25°C

Part Number	Emitting Color	Chip Material	Dominant Wave Length (nm) Typ	Peak Wave Length (nm) Typ	Viewing Angle 2θ1/2 Deg	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
PL00193-WCGR1718	Ultra-Bright Green	AllnGaP	573	576	110°	2.2	2.6	18	45
	Ultra-Bright Red	AllnGaP	635	645		2.1	2.6	45	115

Package Dimensions are in **Millimeters**. Tolerance is ± 0.15mm unless otherwise specified.

