



Formable 250 Semi-rigid Coax Cable with Tinned Copper Braid Outer Conductor

TECHNICAL DATA SHEET

PE-SR401FL

Formable 250 Semi-rigid Coax Cable with Tinned Copper Braid Outer Conductor

Configuration

Inner Conductor Material and Plating Copper, Silver Dielectric Type PTFE

Shield Materials Tinned Copper Braid

Electrical Specifications

Impedance, Ohms50Velocity of Propagation, %69.5Maximum Operating Frequency, GHz18Capacitance, pF/ft [pF/m]29 [95.14]Maximum Operating Voltage, Volts3,500

Electrical Specifications by Frequency

Frequency 1

Frequency, MHz 500

Attenuation, dB/100ft [dB/100m] 5.2 [17.06]

Frequency 2

Frequency, MHz 1000 Attenuation, dB/100ft [dB/100m] 7.6 [24.93]

Frequency 3

Frequency, GHz

Attenuation, dB/100ft [dB/100m] 19.2 [62.99]

Frequency 4

Frequency, GHz

Attenuation, dB/100ft [dB/100m] 29.9 [98.1]

Frequency 5

Frequency, GHz 18

Attenuation, dB/100ft [dB/100m] 44.2 [145.01]

Mechanical Specifications

Temperature

Operating Range, deg C -55 to +125

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Formable 250 Semi-rigid Coax Cable with Tinned Copper Braid Outer Conductor PE-SR401FL

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE-SR401FL CAD Drawing

Formable 250 Semi-rigid Coax Cable with Tinned Copper Braid Outer Conductor

