

75 Ohm BNC Male Connector Crimp/Solder Attachment for RG6



PE4598

RF Connectors Technical Data Sheet

R Q D/LRQ

- BNC Male Connector
- 75 Ohms
- Straight Body Geometry

)HD/MHV

- Max. Operating Frequency 1,000 MHz
- Good VSWR of 1.3:1

- RG6 Interface Type
- Crimp/Solder Attachment
- Gold Plated Brass Contact
- 30 µin minimum contact plating

\$SOLFD/LRQ

General Purpose Test

Custom Cable Assemblies

W

Pasternack's PE4598 75 ohm BNC male connector crimp/solder attachment for RG6 is part of our full line of RF components available for same-day shipping. Our BNC male connector operates up to a maximum frequency of 1,000 MHz and offers good VSWR of 1.3:1.

2MRR1280HFRQFWRU3(GD/DMHWVSHFLED/LR02QGUZZW66LPH02LR02DHVR22HORZ02KV3) 3DWHUEN12FURDFD/DR37I5)PLFURD2QPLOOLPHWHU22FRQFWRUVDOR22GHVL62UVWRFR02HQFXWRPL]H WMLUVL02FRQFWLR02R22MUWMOLNH:MWMUWMQHGLVWRSUR12GH02IRUBRDGGHVL62UVLPSOFUHD/HDXWRP FBOHDVHPEOFR02D/LR02DWHUEN12WMUL12/FRQFWRUIRUWMMRE3D/WHUENF02VRH[SHUWOELOGR02FXWRP cable connector assemblies for you and ship same-day.

(OHFWULFD6SHFL€D/LRQ

0LQPR	7SLFD	᠐ᡛᡅ₽℟	8QWV
&			0+]
		1.3:1	
		500	Vrms
	9	10	& 1.3:1

0HFØFD6SHFL€D/LRQ

6L]H	
Length	1.122 in [28.5 mm]
:LGWKD	L Q P@
Weight	0.028 lbs [12.7 g]

©LFNWHIROORZQLQRUHQHUSDW®EHULG(\$&RBEVLWHWRREWDQGLWLRQSDWLCRUPD/LRCEO/SLOULFH LBQ/RUQFHUWLFD/LRQ 75 Ohm BNC Male Connector Crimp/Solder Attachment for RG6 PE4598

Sales@Pasternack.com • Techsupport@Pasternack.com

1