Rev: 053107



Features

- Provides Snap-In Connection Between SIP Stiks and Motherboard
- **♦ Low Insertion Force, Redundant Contacts**
- **♦** All Connectors are RoHS Compliant

Ordering Information

PART	DESCRIPTION	LENGTH (in)	PITCH (in)	ORIGINAL MANUFACTURER PART # (FOR REFERENCE ONLY)
DS9072 -40V	40 contact, vertical position	2.950	0.050	Molex 15-82-0782
DS9072H-40R	40 contact, high-profile right-angle position	2.950	0.050	Molex 15-82-1528
DS9072-72V	72 contact, vertical position	4.550	0.050	Molex 15-82-0772
DS9072H-72R	72 contact, high-profile right-angle position	4.550	0.050	Molex 15-82-0329
DS9072L-72R	72 contact, low-profile right-angle position	4.550	0.050	Molex 15-82-1303

40-Position DIP-to-SIP and SIP-to-DIP Adaptors for Development of DS2250 Micro Stik Products

PART	DESCRIPTION	PITCH (in)	ADAPTOR
DS9075 -40V	40 contact, horizontal DIP plug with 40 contact, low-profile vertical position SIMM connector	0.050	SIP-to-DIP
DS9076 -40	40 contact, vertical SIMM edge card with 40 contact, vertical DIP socket	0.050	DIP-to-SIP

Maxim Integrated Products 1

Some revisions of this device may incorporate deviations from published specifications known as errata. Multiple revisions of any device may be simultaneously available through various sales channels. For information about device errata, go to: www.maxim-ic.com/errata. For pricing, delivery, and ordering information, please contact Maxim/Dallas Direct! at 1-888-629-4642, or visit Maxim's website at www.maxim-ic.com.