



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

| | | |
|--------------|-----------|---|
| According to | SMC side: | IEC 60169-9, CECC 22140, US MIL-C-39012 |
| | SMA side: | IEC 60169-15; EN 122110; MIL-STD-348A, Fig. 310 |

Documents

N/A

Material and plating

Connector parts

- Center contact
- Outer contact SMC side
- Outer contact SMA side
- Dielectric
- Coupling nut SMC

Material

- CuBe or equivalent
- Brass
- CuBe or equivalent
- PTFE
- Brass

Plating

- Auro Dur, gold plated
- Auro Dur, gold plated
- Auro Dur, gold plated
- Gold, 0.1 µm min.

ADAPTOR
SMC JACK – SMA JACK

39K132-K00L5

Electrical data

| | |
|---------------------------|--|
| Impedance | 50 Ω |
| Frequency | DC to 6 GHz |
| Return loss | ≥ 35 dB, DC to 1 GHz ≥ 30 dB, 1 to 3 GHz ≥ 20 dB, 3 to 6 GHz |
| Insertion loss | ≤ 0.05 √f(GHz) x dB |
| Insulation resistance | ≥ 1x10 ³ MΩ |
| Center contact resistance | ≤ 5 mΩ, SMC side ≤ 3 mΩ, SMA side |
| Outer contact resistance | ≤ 2.5 mΩ, SMC side ≤ 2 mΩ, SMA side |
| Test voltage | 750 V rms, 50 Hz, at sea level |
| Working voltage | ≤ 250 V rms, 50 Hz, at sea level |
| RF-leakage | ≥ 90 dB up to 1 GHz |

Mechanical data

| | | |
|-----------------------------------|--------------------|------------------|
| | SMC side | SMA side |
| Mating cycles | min. 500 | min. 500 |
| Coupling nut retention | ≥ 150 N | N/A |
| Coupling test torque | max. 0.71 Nm | max. 1.7 Nm |
| Recommended torque | 0.25 Nm to 0.35 Nm | 0.8 Nm to 1.1 Nm |
| Center contact captivation: axial | ≥ 10 N | ≥ 10 N |

Environmental data

| | |
|---------------------|---------------------------------|
| Temperature range | -55°C to +155°C |
| Thermal shock | MIL-STD-202, Meth. 107, Cond. B |
| Vibration | MIL-STD-202, Meth. 204, Cond. D |
| Moisture resistance | MIL-STD-202, Meth. 106 |
| Corrosion | MIL-STD-202, Meth. 101, Cond B |
| RoHS | compliant |

Tooling

N/A

Suitable cables

N/A

Weight

Weight 5.8 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

| | | | | | | | |
|--|----------|-------------------|----------|------|--|-----------|---------------|
| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
| Inge Mühlauer | 21/12/04 | Sa. Krautenbacher | 17.03.14 | e00 | 14-0352 | T. Krojer | 17.03.14 |
| Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de | | | | | Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de | | Page 2 / 2 |