



Applications	Commercial Grade	
	Shield Magnetic Shield	
Feature	Multilayer Multilayer	
	Ferrite Core	
Series   Type	MLZ	
Status	Production	
Brand	ТДК	

Size		
Length(L)	1.60mm ±0.15mm	
Width(W)	0.80mm ±0.15mm	
Thickness(T)	0.80mm ±0.15mm	
Recommended Land Pattern (A)	0.60mm Nom.	
Recommended Land Pattern (B)	0.80mm Nom.	
Recommended Land Pattern (C)	0.80mm Nom.	

Electrical Characteristics				
Inductance	$1\mu$ H ±20% at 2MHz			
Rated Current (L Change) [Typ.]				
Rated Current (L Change) [Max.]	140mA (50% Down)			
Rated Current (Temperature Rise) [Typ.]	700mA (20°C Rise)			
Rated Current (Temperature Rise) [Max.]	140mA (20°C Rise)			
DC Resistance [Typ.]	110mΩ			
DC Resistance [Max.]	143mΩ			
Self Resonant Frequency [Min.]				
Self Resonant Frequency [Typ.]				
Q [Min.]				
Q [Typ.]				


Other		
Operating Temp. Range (Including Self-Temp. Rise)	-55 to 125°C	
	Wave (Flow)	
Soldering Method	Reflow	
	Iron Soldering	
AEC-Q200	No	
Packing	Punched (Paper)Taping [180mm Reel]	
Package Quantity	4000pcs	
Whannes are for reference only and show exemplary products. I This PDF document was created based on the data listed on the TDK Corporation website.	0.004g	

! All specifications are subject to change without notice.




## MLZ1608N1R0LT000






# Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)


1k




Rac

#### MLZ1608N1R0LT000





#### MLZ1608N1R0LT000



! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.


Copyright(c) TDK Corporation. All rights reserved.



## MLZ1608N1R0LT000



# Associated Images



! Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.