



## 13003DH

Preliminary

**NPN SILICON TRANSISTOR**

### NPN SILICON BIPOLAR TRANSISTORS FOR LOW FREQUENCY AMPLIFICATION

#### DESCRIPTION


The UTC **13003DH** is a silicon NPN power switching transistor; it uses UTC's advanced technology to provide customers high collector-base breakdown voltage, low reverse leakage current and high reliability, etc.

The UTC **13003DH** is suitable for electronic ballast power switch circuit and the compact electronic energy-saving light.

#### FEATURES

- \* High collector-base breakdown voltage
- \* Low reverse leakage current
- \* High reliability

#### EQUIVALENT CIRCUIT




#### ORDERING INFORMATION




Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
13003DHL-x-TM3-T	13003DHG-x-TM3-T	TO-251	B	C	E	Tube
13003DHL-x-T60-K	13003DHG-x-T60-K	TO-126	B	C	E	Bulk
13003DHL-x-T92-B	13003DHG-x-T92-B	TO-92	E	C	B	Tape Box
13003DHL-x-T92-K	13003DHG-x-T92-K	TO-92	E	C	B	Bulk

Note: Pin Assignment: B: Base C: Collector E: Emitter

<p>13003DHL-x-TM3-T</p> <ul style="list-style-type: none"> <li>(1) Packing Type</li> <li>(2) Package Type</li> <li>(3) Rank</li> <li>(4) Lead Free</li> </ul>	<ul style="list-style-type: none"> <li>(1) T: Tube, B: Bluk, K: Bulk</li> <li>(2) TM3: TO-251, T60: TO-126, T92: TO-92</li> <li>(3) x: refer to Classification of <math>h_{FE}</math></li> <li>(4) L: Lead Free, G: Halogen Free</li> </ul>
---	---



■ MARKING INFORMATION

PACKAGE	MARKING
TO-251	 <p>UTC 13003DH □ □□□□□□ □ Lot Code ← □□□□□□ → Data Code 1</p> <p>L: Lead Free P: Halogen Free</p>
TO-126	 <p>UTC □□□□ □ 13003DH □ 1</p> <p>Data Code L: Lead Free P: Halogen Free</p>
TO-92	 <p>UTC 13003DH □ □□ □ 1</p> <p>L: Lead Free P: Halogen Free Data Code</p>

■ ABSOLUTE MAXIMUM RATINGS ( $T_A=25^\circ\text{C}$ , unless otherwise noted)

PARAMETER	SYMBOL	RATINGS	UNIT	
Collector-Base Voltage	$V_{CBO}$	600	V	
Collector-Emitter Voltage	$V_{CEO}$	400	V	
Emitter-Base Voltage	$V_{EBO}$	9	V	
Continuous Collector Current	$I_C$	1.8	A	
Power Dissipation	$P_D$	$T_A=25^\circ\text{C}$	1.25	W
		$T_C=25^\circ\text{C}$	50	W
Junction Temperature	$T_J$	150	$^\circ\text{C}$	
Storage Temperature Range	$T_{STG}$	-55~+150	$^\circ\text{C}$	

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS ( $T_A=25^\circ\text{C}$ , unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Base Breakdown Voltage	$BV_{CBO}$	$I_C=0.1\text{mA}$	600			V
Collector-Emitter Breakdown Voltage	$BV_{CEO}$	$I_C=1\text{mA}$	400			V
Emitter-Base Breakdown Voltage	$BV_{EBO}$	$I_E=0.1\text{mA}$	9			V
Collector Cut-Off Current	$I_{CBO}$	$V_{CB}=600\text{V}, I_E=0$			0.1	mA
Collector-Emitter Cut-Off Current	$I_{CEO}$	$V_{CE}=400\text{V}, I_B=0$			0.1	mA
Emitter-Base Cut-Off Current	$I_{EBO}$	$V_{EB}=9\text{V}, I_C=0$			0.1	mA
DC Current Gain (Note 1)	$h_{FE}$	$I_C=0.2\text{A}, V_{CE}=5.0\text{V}$	15		30	
Low current and high current $h_{FE2}$ $h_{FE1}$ ratio	$h_{FE1}/h_{FE2}$	$h_{FE1}: V_{CE}=5\text{V}, I_C=5\text{mA}$	0.75	0.9		
		$h_{FE2}: V_{CE}=5\text{V}, I_C=0.2\text{A}$				
Collector-Emitter Saturation Voltage (Note)	$V_{CE(SAT)}$	$I_C=1\text{A}, I_B=0.25\text{A}$		0.30	0.8	V
Base-Emitter Saturation Voltage (Note)	$V_{BE(SAT)}$	$I_C=1\text{A}, I_B=0.25\text{A}$		0.9	1.2	V
Storage Time	$t_s$	UI9600, $I_C=0.1\text{A}$	3		5	$\mu\text{s}$
Rise Time	$t_R$				1	$\mu\text{s}$
Fall Time	$t_F$				1	$\mu\text{s}$
Transition Frequency	$f_T$	$I_C=0.1\text{A}, V_{CE}=10\text{V}, f=1\text{MHz}$	5			MHz
Diode Forward Voltage	$V_F$	$I_F=1.5\text{A}$			2.5	V

Note: Pulse test, pulse width  $t_p \leq 300\mu\text{s}$ , Duty cycle  $\leq 2\%$

■ CLASSIFICATION OF  $h_{FE}$

RANK	A	B	C
RANGE	15 ~ 20	20 ~ 25	25 ~ 30

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.