


RoHS Compliant Product
A suffix of "-C" specifies halogen & lead-free

FEATURES

- I_o : 2A
- V_{RRM} : 50~1000V
- Glass passivated chip
- High surge forward current capability

APPLICATIONS

- General purpose 1 phase Bridge rectifier applications



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	13.3	14.3	G	13.1	13.5
B	10.3	11.3	H	3.7	3.9
C	6.4	7.4	J	2.0	2.2
D	4.5	5.5	K	0.4	0.6
E	1.05	1.45	L	2.6	3.6
F	0.60	0.85	M	3.1	3.4

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Rating 25°C ambient temperature unless otherwise specified. Single phase half wave, 60Hz, resistive or inductive load.
For capacitive load, de-rate current by 20%.)

Parameter	Symbol	Part Number							Unit
		D2UB 05	D2UB 10	D2UB 20	D2UB 40	D2UB 60	D2UB 80	D2UB 100	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Average Rectified Output Current @ 60Hz sine wave, R-load	Without heatsink $T_A=29^\circ\text{C}$	1.2							A
	With heatsink $T_c=140^\circ\text{C}$	2.0							
Surge(Non- repetitive)Forward Current @ 60Hz sine wave, 1 cycle, $T_J=25^\circ\text{C}$	I_{FSM}	60							A
Current Squared Time ¹	I^2t	15							A ² S
Dielectric Strength@ Terminals to case , AC 1 minute	V_{DIS}	2							KV
Mounting Torque@ Recommend torque : 5kg.cm	Tor	8							Kg.cm
Peak Forward Voltage@ $I_{FM}=1.0A$, Pulse measurement, Rating of per diode	V_{FM}	1.05							V
Peak Reverse Current@ $V_{RM}=V_{RRM}$, Pulse measurement, Rating of per diode	I_{RRM}	10							μA
Thermal Resistance	Without heatsink	55							°C / W
	With heatsink	1.5							
Junction and Storage temperature range	T_J, T_{STG}	-55~+150							°C

Notes :

1. $1\text{ms} \leq t < 8.3\text{ms}$ $T_J=25^\circ\text{C}$, Rating of per diode

RATINGS AND CHARACTERISTIC CURVES

FIG1:Io-Tc Curve




FIG2: Surge Forward Current Capability




FIG3: Forward Voltage




FIG4: Typical Reverse Characteristics

