

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

## **Features**

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisure Sensitivity Level 1
- General Purpose Switching and Amplification
- Capable of 0.8Watts of Power Dissipation.
- Collector-current 0.7A
- Collector-base Voltage 80V
- Marking : C1008
- Halogen free available upon request by adding suffix "-HF"

### Electrical Characteristics @ 25°C Unless Otherwise Specified


Symbol	Parameter	Min	Max	Units			
OFF CHARACTERISTICS							
V <sub>(BR)CEO</sub>	Collector-Emitter Breakdown Voltage* (I <sub>c</sub> =10mAdc, I <sub>в</sub> =0)	60		Vdc			
V <sub>(BR)CBO</sub>	Collector-Base Breakdown Voltage (I <sub>c</sub> =100µAdc, I <sub>E</sub> =0)	80		Vdc			
V <sub>(BR)EBO</sub>	Emitter-Base Breakdown Voltage (I <sub>E</sub> =10µAdc, I <sub>C</sub> =0)	8		Vdc			
Сво	Collector Cutoff Current (V <sub>CB</sub> =60Vdc, <u>k</u> =0Adc)		0.1	µAdc			
I <sub>EBO</sub>	Emitter Cutoff Current (V <sub>EB</sub> =5.0Vdc, <sub>L</sub> =0Adc)		0.1	µAdc			

### **ON CHARACTERISTICS**

h <sub>FE</sub>	DC Current Gain*						
	(l <sub>c</sub> =50mAdc, V	<sub>CE</sub> =2.0Vdc)	40	400			
V <sub>CE(sat)</sub>	Collector-Emitter						
	(l <sub>c</sub> =500mAdc, l	<sub>B</sub> =50mAdc)		0.4	Vdc		
V <sub>BE(sat)</sub>	Base-Emitter Sa		1.1	Vdc			
C <sub>ob</sub>	Collector Output Capacitance		Ти	Typ 8			
Oob	(V <sub>CB</sub> =10Vdc,Ic	T y	тур б				
SMALL-SIGNAL CHARACTERISTICS							
f <sub>T</sub>	Transistor Frequency						
	(L=50mAdc, V <sub>CE</sub> =10Vdc)		30		MHz		
CLASSIFICATION OF Hern							
Rank	R	0	Y		G		
Range	40-80	70-140	120-240	20-240 200-400			

## 2SC1008-R 2SC1008-O 2SC1008-Y 2SC1008-G

**NPN Silicon** 



www.mccsemi.com



### **Ordering Information :**

Device	Packing	
Part Number-AP	Ammo Packing: 2Kpcs/Ammo Box	
Part Number-BP	Bulk: 100Kpcs/Carton	

Note : Adding "-HF" suffix for halogen free, eg. Part Number-AP-HF

### **\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# www.mccsemi.com