



SAW Components

SAW RF filter for base stations

R-GSM

Series/type: B5057
Ordering code: B39941B5057U410

Date: June 24, 2014
Version: 2.1


© EPCOS AG 2015. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

EPCOS AG is a TDK Group Company.


Data sheet

Application


- Low-loss filter for Basestation R-GSM, transmit path (Tx)
- Usable passband 39 MHz
- Unbalanced to unbalanced operation
- No matching required
- Filter impedance 50 Ω


Features

- Package size 3.0 x 3.0 x 1.1 mm³
- Package code DCC6C
- Approximate weight 0.037 g
- Ceramic package for **Surface Mount Technology (SMT)**
- RoHS compliant
- Ni, gold-plated
- **Electrostatic Sensitive Device (ESD)**
- **Moisture Sensitivity Level 1**
- Filter surface passivated


Pin configuration

- 2 Input
- 5 Output
- 1, 3, 4, 6 To be grounded



SAW Components
B5057
SAW RF filter
940.5 MHz
Data sheet

Characteristics

Temperature range for specification:	T = -30 °C to +80 °C
Terminating source impedance:	Z _S = 50 Ω
Terminating load impedance:	Z _L = 50 Ω

		min.	typ. @ 25 °C	max.	
Center frequency	f _C	—	940.5	—	MHz
Maximum insertion attenuation	α _{max}	—	2.7	4.0 ¹⁾	dB
921.0 ... 960.0 MHz					
Amplitude ripple (p-p)	Δα	—	1.4	3.0 ²⁾	dB
921.0 ... 960.0 MHz					
Input VSWR		—	2.3:1	3.0:1 ³⁾	
921.0 ... 960.0 MHz					
Output VSWR		—	2.6:1	3.0:1 ⁴⁾	
921.0 ... 960.0 MHz					
Absolute attenuation	α _{abs}				
0.3 ⁵⁾ ... 800.0 MHz		25	47	—	dB
800.0 ... 880.0 MHz		26	39	—	dB
880.0 ... 905.0 MHz		20 ⁶⁾	31	—	dB
905.0 ... 915.0 MHz		2 ⁷⁾	6	—	dB
980.0 ... 985.0 MHz		23	42	—	dB
985.0 ... 1005.0 MHz		30	34	—	dB
1005.0 ... 1025.0 MHz		30	34	—	dB
1025.0 ... 1760.0 MHz		27	34	—	dB
1760.0 ... 2000.0 MHz		28	32	—	dB
2000.0 ... 4000.0 MHz		18	23	—	dB

1) 3.0 dB at 25 °C.

2) 2.0 dB at 25 °C.

3) 2.8 at 25 °C.

4) 2.8 at 25 °C.

5) Final electrical test starts at 10 MHz.

6) 28 dB at 25 °C.

7) 3 dB at 25 °C.

Maximum ratings

Operable temperature range	T	-40/+85	°C	
Storage temperature range	T _{stg}	-40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	125 ¹⁾	V	Machine Model
		350 ²⁾	V	Human Body Model
		1000 ³⁾	V	Charged Device Model
Input power 921.0 ... 960.0 MHz	P _{IN}	10	dBm	cw

1) acc. to JESD22-A115B (MM - Machine Model), 10 negative & 10 positive pulses


2) acc. to JESD22-A114F (HBM - Human Body Model), 1 negative & 1 positive pulses

3) acc. to JESD22-C101C (CDM - Field Induced Charged Device Model), 3 negative & 3 positive pulses


Data sheet

SMD

Transfer function (S21, narrowband)



Transfer function (S21, wideband)




Please read *cautions and warnings* and *important notes* at the end of this document.

Data sheet




Smith charts

S₁₁ function



S₂₂ function



SAW Components	B5057
SAW RF filter	940.5 MHz

Data sheet



References

Type	B5057
Ordering code	B39941B5057U410
Marking and package	C61157-A7-A67
Packaging	F61074-V8168-Z000
Date codes	L_1126
S-parameters	B5057_NB.s2p B5057_WB.s2p see file header for port/pin assignment table
Soldering profile	S_6001
RoHS compatible	RoHS-compatible means that products are compatible with the requirements according to Art. 4 (substance restrictions) of Directive 2011/65/EU of the European Parliament and of the Council of June 8th, 2011, on the restriction of the use of certain hazardous substances in electrical and electronic equipment ("Directive") with due regard to the application of exemptions as per Annex III of the Directive in certain cases.
Matching coils	See Inductor pdf-catalog http://www.tdk.co.jp/tefe02/coil.htm#aname1 and Data Library for circuit simulation http://www.tdk.co.jp/etvcl/index.htm for a large variety of matching coils.

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG
Systems, Acoustics, Waves Business Group
P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2014. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CeraLink, CeraPlas, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FilterCap, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, TFAP, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.