




RoHS
COMPLIANCE



Features

- ✦ Plastic material used carriers Underwriters Laboratory Classification 94V-0
- ✦ Metal silicon junction, majority carrier conduction
- ✦ Low power loss, high efficiency
- ✦ High current capability, low forward voltage drop
- ✦ High surge capability
- ✦ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- ✦ Guard-ring for overvoltage protection
- ✦ High temperature soldering guaranteed: 260°C/10 seconds, 0.25"(6.35mm) from case
- ✦ Green compound with suffix "G" on packing code & prefix "G" on datecode



Mechanical Data

- ✦ Cases: JEDEC TO-220AB molded plastic
- ✦ Terminals: Pure tin plated, lead free, solderable per MIL-STD-750, Method 2026
- ✦ Polarity: As marked
- ✦ Mounting position: Any
- ✦ Mounting torque: 5 in. - lbs, max
- ✦ Weight: 1.71 grams

Dimensions in inches and (millimeters)

Marking Diagram



- MBR20XXCT = Specific Device Code
- G = Green Compound
- Y = Year
- WW = Work Week

Maximum Ratings and Electrical Characteristics

Rating at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	MBR 2035 CT	MBR 2045 CT	MBR 2050 CT	MBR 2060 CT	MBR 2090 CT	MBR 20100 CT	MBR 20150 CT	MBR 20200 CT	Units	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	35	45	50	60	90	100	150	200	V	
Maximum RMS Voltage	V_{RMS}	24	31	35	42	63	70	105	140	V	
Maximum DC Blocking Voltage	V_{DC}	35	45	50	60	90	100	150	200	V	
Maximum Average Forward Rectified Current	$I_{F(AV)}$	20								A	
Peak Repetitive Forward Current (Rated VR, Square Wave, 20KHz)	I_{FRM}	20								A	
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	150								A	
Peak Repetitive Reverse Surge Current (Note 1)	I_{RRM}	1.0		0.5					A		
Maximum Instantaneous Forward Voltage at: (Note 2) IF=10A, TA=25°C IF=10A, TA=125°C IF=20A, TA=25°C IF=20A, TA=125°C	V_F	-	0.57	0.80	0.70	0.85	0.75	0.99	0.87	V	
Maximum Instantaneous Reverse Current @ TA=25 °C at Rated DC Blocking Voltage @ TA=125 °C	I_R	15		10		5			0.15	mA	
Voltage Rate of Change (Rated V_R)	dV/dt	10000								V/uS	
Typical Junction Capacitance	C_j	400			320					pF	
Typical Thermal Resistance Per Leg	$R_{\theta JC}$	1.0				2.0					°C/W
Operating Temperature Range	T_J	- 65 to + 150								°C	
Storage Temperature Range	T_{STG}	- 65 to + 175								°C	

Note 1: 2.0uS Pulse Width, f=1.0KHz

Note 2: Pulse Test : 300uS Pulse Width, 1% Duty Cycle

RATINGS AND CHARACTERISTIC CURVES (MBR2035CT THRU MBR20200CT)

FIG. 1- FORWARD CURRENT DERATING CURVE




FIG. 2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS PER LEG




FIG. 4- TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG. 5- TYPICAL JUNCTION CAPACITANCE




FIG. 6- TYPICAL TRANSIENT THERMAL IMPEDANCE PER LEG

