

Type 288P Orange Drop[®] R-C Arc Suppressor Network

Features

- Designed for arc and transient suppression. Extends life of relays, switches, triacs and related products.
- Low cost, single low-profile package, Radial-lead.
- Metallized polyester film capacitor and low value $\frac{1}{2}$ watt carbon composition resistor connected in series.



Specifications

Capacitance Values:

.1, .22 and .47 μ F

Resistor Values:

47, 100 and 470 Ohms

Tolerance:

$\pm 10\%$ for both capacitor and resistor.

Voltage Rating:

400 Volts D-C/250 Volts A-C

Insulation Resistance:

10,000 M Ω minimum at +25°C

Operating Temperature Range:

-40°C to +85°C

Capacitor Section:

Metallized polyester film.

Resistor:

$\frac{1}{2}$ watt carbon composition

Capacitor Lead Wire:

Tinned copper-clad steel,
0.032 (0.8) diameter, #20 AWG

Resistor Lead Wire:

Tinned copper,
0.028 (0.7) diameter, #22 AWG

Encapsulation:

Conformal coating of flame retardant orange epoxy (meets UL94V-2 specifications).

A-C Voltage Operation:

250 Volts RMS, maximum. Sum of D-C and peak A-C voltages not to exceed D-C rating of 400 VDC.


Humidity Test:

Units subjected to 95% relative humidity at +75°C for 72 hours with no voltage applied. After drying, minimum IR shall be 5000 M Ω at +25°C and 400 VDC.


Dimensions in inches, metric (mm) in parenthesis.

Type 288P, Orange Drop[®], R-C Network Arc Suppressors

Ordering/Part Number Information



Dimensions



Standard Marking Format

Marking

CDE 288P400V
 104K 100 ohm
 0515 R

Description

CDE CDE Electronics identification
 288P Type number
 400V D-C Voltage rating, Volts
 104K Capacitance and tolerance code (EIA tolerance code, K = ±10%)
 100 ohm Resistor value in ohms
 0515 Weekly date code (i.e. 15th week of 2005)
 R Indicates resistor side of network

Type 288P Standard Sizes/Ratings - 400 VDC/250 VAC*

Cap Value, μF	Resistor, Ω	Part Number ¹	L	T	H	S
0.1	100	288P10494J101	1.000 (25.4)	.46 (11.7)	.63 (16.0)	.691 (17.6)
0.1	470	288P10494J471	1.000 (25.4)	.46 (11.7)	.63 (16.0)	.691 (17.6)
0.22	100	288P22494H101	1.125 (28.6)	.37 (9.4)	.59 (15.0)	.817 (20.8)
0.22	470	288P22494H471	1.125 (28.6)	.37 (9.4)	.59 (15.0)	.817 (20.8)
0.47	47	288P47494K470	1.437 (36.5)	.41 (10.4)	.63 (16.0)	1.129 (28.7)
0.47	100	288P47494K101	1.437 (36.5)	.41 (10.4)	.63 (16.0)	1.129 (28.7)

* Voltage rating at 60 Hz, RMS

Dimensions in inches, metric (mm) in parenthesis.

Notice and Disclaimer: All product drawings, descriptions, specifications, statements, information and data (collectively, the "Information") in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements ("Cornell Dubilier") has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any guarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly disclaims any guarantee, warranty or representation concerning the suitability for a specific customer application, use, storage, transportation, or operating environment. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by Cornell Dubilier with reference to the use of any Cornell Dubilier products is given gratis (unless otherwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the advice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design and manufacturing of its products, in light of the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage. Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated in such warnings, cautions and notes, or that other safety measures may not be required.