



LED PARAMETER	FORWARD CURRENT	FORWARD VOLTAGE @ 20mA	LUMINOUS INTENSITY
UNITS	mA	V	mcd
YELLOW	20	2.1 - 2.6	100

NOTE:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
- TERMINAL NUMBERS FOR REF ONLY
- CIRCUIT: SPST OFF-MOMENTARY ON
- CONTACT MATERIAL: Gold over SILVER
- RATING: 125mA @ 125 VAC
100mA @ 50 VDC
- ELECTRIC LIFE: 500,000 CYCLES AT FULL LOAD
- CONTACT RESISTANCE: 50 milli-OHM max. (INITIAL)
- INSULATION RESISTANCE: 1,000 MEGA-OHM min. @ 500VDC
- DIELECTRIC STRENGTH: 1,000 VAC rms.
- OPERATING FORCE: 350 gf +/- 150 gf
- OPERATING TEMPERATURE: -30°C to +85°C
- CONTACT BOUNCE: 10ms MAX.
- TRAVEL: 1.5mm
- PANEL THICKNESS RANGE: 0.8 - 1.8mm
- ▲ DENOTES CRITICAL PARAMETER.
- 2011/65/EU (ROHS) COMPLIANT
- HARDWARE INCLUDED:
 - T081100 RUBBER SEAL (1)
- SEAL RATING: IP67 AT THE FRONT PANEL

G	23328	note 15 to .8 - 1.8mm	4/25/18	MW
F	22441	ADDED BOTTOM VIEW	8/11/16	MJR
E	21594	CHANGE NOTE 19: IP67 WAS IP65	9/24/14	EBP
REV	PCR NO	DESCRIPTION	DATE	BY



TITLE RP8100B1M1CEBLKWHTYEL				
SCALE	DATE	DR	DWG	REV
3:2	2/20/2009	BLR	ST081031	G