



SMB Plug Connector Solder Attachment Thru Hole
PCB, .200 inch x .067 inch Hole Spacing

RF Connectors Technical Data Sheet

PE4366

ROWLRQ

- SMB Plug Connector
- MIL-STD-348
- 50 Ohms

- Straight Body Geometry
- Thru Hole Interface Type
- Solder Attachment

)HDWV

- Gold Plated Contact

- Contact plating according to MIL-G-45204

\$SOLFDWLRQ

- General Purpose Test
- PCB Applications



Pasternack's PE4366 SMB plug connector with solder attachment for thru hole PCB (.200 inch x .067 inch hole spacing) is part of our full line of RF components available for same-day shipping.

20% SOXFRWU (GDWDVHW VSHLEFDWLRQDGDZGGLPHQDHRVZHORZWKV 3) 3DVWHDFMEBDGFDWDORR15)PLFBDMQPLOOLPHWHDFRQFWRVDOORZGHVLEUWRFRDGFWRPLJH their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom FDEOHDVVHPEOFRQWLRQDVWHQDFVWKLWFRQFWRURWKIMRE3DVWHQDFDQOVRHJSHWOEKOGREXWRP cable assemblies for you and ship same-day.

0HFQFDO6SHFLEFDWLRQ

6LJH	
Length	0.467 in [11.86 mm]
Width/Dia.	0.25 in [6.35 mm]
Height	0.25 in [6.35 mm]
Weight	0.005 lbs [2.27 g]

0DWHLD06SHFLEFDWLRQ

HVFLSWLRQ	0DWHLD0	30DWLQ
Contact		Gold MIL-G-45204
Insulation	PTFE	
Body	Brass	Gold MIL-G-45204

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, [LQVWDFHLEFDWLRQ SMB Plug Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing PE4366](#)



