

FEATURES

- High Efficiency & Long Life
- Worldwide Input Range
- Compact Size
- Optimized Performance
- Fully Isolated & SELV
- Protections: Short Circuit/ Open Circuit/ Over Voltage/ Over Temperature
- Class 2 power unit



PRODUCT HIGHLIGHT

Output Voltage/Current Max 24V/700mA
:

SPECIFICATION

Model Name	FSP015-DZ24CE(070)		
Wattage	17W		
Dimming	Non-Dimming		
Input Electrical Specification	Input Voltage	200~240 Vac	
	Input Frequency	47~63 Hz	
	PFC	≥0.9	
Constant Current / Constant Voltage	Constant Current		
Output Voltage and Current Rating	Output1	16-24 V , 700 mA	
	Efficiency	≥ 80 %	
Output Electrical Specification	Life	50,000 hours without system & full load.@230Vac & ambient 40°C	
	Protection Function	OVP,OTP,SCP,OCP	
Environmental Requirement	TEMP. Range	Operating : 0°C to +40°C Storage : -20°C to +60°C	
	Insulation	Primary to Secondary: 500Vdc,25M ohms min.	
EMC performance	EN55015	Class B Conducted, Class B radiated	
	EN55022	Class B Conducted, Class B radiated	
	EN61000-3-2	A	
	EN61000-4-3	1	
Dimension	78.5mm(L) x 51.8mm(W)x 31.5mm(H)		

PROTECTION FUNCTIONS

OVP,OTP,SCP,OCP

This content is subject to change, please refer to specification for more detail.
FSP reserve the right to change the content without prior notice