

Remote Power Controllers Up to 200 Amps • Form X Magnetic Latching For AC only applications

SPECIFICATIONS

GENERAL

Contact ArrangementSPST (1 Form X)
Weight15 oz max.
 Designed to meet the requirements of MIL-C-83383

PERFORMANCE

Contact Ratings (Note 1):

Power Contacts:

All loads.....Up to 200 Amps @ 115 VAC

<u>Current Trip Points</u>	<u>Trip Time</u>
1000% of Rated Current1.0 Sec. max.
400% of Rated Current10.0 Sec. max.
200% of Rated Current60.0 Sec. max.
138% of Rated Current1.0 Hour max.
Up to 115% of Rated CurrentNo Trip

Tolerances:

Current±10%
 Time±10%

Auxiliary Contacts:

Configuration.....SPDT
 Current Rating5 Amps @ 28 VDC

Life50,000 cycles @ rated Res. and Ind. load
 25,000 cycles @ rated Motor load
 100,000 cycles mechanical

Notes:

- For other ratings or calibrations consult the factory.
- For applications requiring higher shock and vibration, consult the factory.

Rupture (main contacts)3600 Amperes

Response Time:12 ms nom.

Contact Bounce Time2 ms max
 @ rated contact load, 115 VAC

Contact Voltage Drop:

Initial225 mv @ Rated Current
 End of Life250 mv @ Rated Current

Operating Voltage:

Nominal AC Voltage104 to 122 VAC

ENVIRONMENTAL

Temperature Range-54°C to +71°C

Vibration (Note 2).....10 G'S 50 - 2000 Hz

Shock (Operating)(Note 2)25 G's 11 ms

Acceleration15 G

ELECTRICAL CHARACTERISTICS

Duty Cycle.....Intermittent

Insulation Resistance100 megohms
 @ 500V 25°C

Dielectric Strength:

Sea Level:


Contact to Case1,500 VRMS
 Contact to Coil1,500 VRMS
 Coil to Case1,500 VRMS
 Across Open Contacts1,350 VRMS

50,000 Feet:

All Points500 VRMS


The 700 Remote Power Controllers are designed to sense the current level flowing through their contacts, and to open the circuit when the current exceeds the specified current rating. These units use our unique magnetic latching motor design to minimize power consumption. These units are fully temperature compensated for accurate operation over the full temperature range.

The 700 circuitry has 1500 watts of Peak Power Dissipation transient suppression built in so it can withstand the rigors of even the noisiest of supply voltages. Utilizing all space age approved materials, the 700 Remote Power Controllers are ideal for demanding applications.



OVERALL DIMENSIONS

SELECTION TABLE






Catalog Number	Continuous Ampere Contact Rating	Thread "B"	Dimension "A"
700-5()	5	10-32 UNF	.500
700-7.5()	7.5	10-32 UNF	.500
700-10()	10	10-32 UNF	.500
700-15()	15	10-32 UNF	.500
700-20()	20	10-32 UNF	.500
700-25()	25	10-32 UNF	.500
700-35()	35	1/4-28 UNF	.610
700-40()	40	1/4-28 UNF	.610
700-50()	50	1/4-28 UNF	.610
700-60()	60	1/4-28 UNF	.610
700-75()	75	1/4-28 UNF	.610
700-100()	100	1/4-28 UNF	.610
700-125()	125	1/4-28 UNF	.610
700-150()	150	1/4-28 UNF	.610
700-175()	175	1/4-28 UNF	.610
700-200()	200	1/4-28 UNF	.610

SCHEMATIC

TYPICAL WIRING DIAGRAM

TRIP TIME CURVE



GENERAL NOTES

- Unless otherwise specified, all tests made at nominal coil voltages, @ 25°C.
- For special coil variations, switching configurations, terminals styles and mounting types, consult the factory.
- Unless otherwise specified, tolerances on decimal dimensions are ± .010".
- Specifications contained herein are subject to change without notice.



Microsemi Corporate Headquarters

One Enterprise, Aliso Viejo,
CA 92656 USA

Within the USA: +1 (800) 713-4113

Outside the USA: +1 (949) 380-6100

Sales: +1 (949) 380-6136

Fax: +1 (949) 215-4996

E-mail: sales.support@microsemi.com

© 2015 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

Microsemi Corporation (MSCC) offers a comprehensive portfolio of semiconductor and system solutions for communications, defense & security, aerospace and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, Calif., and has approximately 3,600 employees globally. Learn more at www.microsemi.com.

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.