

Isc N-Channel MOSFET Transistor

STP75NF75FP

• FEATURES

- Excellent switching performance
- With low gate drive requirements
- Easy to drive
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

• APPLICATIONS



- Switching application

• ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

| SYMBOL | PARAMETER | VALUE | UNIT |
|-----------|---|----------|------|
| V_{DSS} | Drain-Source Voltage | 75 | V |
| V_{GSS} | Gate-Source Voltage | ± 20 | V |
| I_D | Drain Current-Continuous@ $T_c=25^\circ\text{C}$ $T_c=100^\circ\text{C}$ | 80 70 | A |
| I_{DM} | Drain Current-Single Pulsed | 320 | A |
| P_D | Total Dissipation | 45 | W |
| T_j | Operating Junction Temperature | -55~175 | °C |
| T_{stg} | Storage Temperature | -55~175 | °C |

• THERMAL CHARACTERISTICS

| SYMBOL | PARAMETER | MAX | UNIT |
|----------------|---------------------------------------|------|------|
| $R_{th(ch-c)}$ | Channel-to-case thermal resistance | 3.33 | °C/W |
| $R_{th(ch-a)}$ | Channel-to-ambient thermal resistance | 62.5 | °C/W |



Isc N-Channel MOSFET Transistor**STP75NF75FP****ELECTRICAL CHARACTERISTICS** $T_c=25^\circ\text{C}$ unless otherwise specified

| SYMBOL | PARAMETER | CONDITIONS | MIN | TYP | MAX | UNIT |
|----------------------------|--------------------------------|--|-----|-----|-----------|------------------|
| BV_{DSS} | Drain-Source Breakdown Voltage | $\text{V}_{\text{GS}}=0\text{V}; \text{I}_D= 1\text{mA}$ | 75 | | | V |
| $\text{V}_{\text{GS(th)}}$ | Gate Threshold Voltage | $\text{V}_{\text{DS}}=\pm 20\text{V}; \text{I}_D=0.25\text{mA}$ | 2 | | 4 | V |
| $\text{R}_{\text{DS(on)}}$ | Drain-Source On-Resistance | $\text{V}_{\text{GS}}= 10\text{V}; \text{I}_D=40\text{A}$ | | 9.5 | 11 | $\text{m}\Omega$ |
| I_{GSS} | Gate-Source Leakage Current | $\text{V}_{\text{GS}}= \pm 20\text{V}; \text{V}_{\text{DS}}= 0\text{V}$ | | | ± 0.1 | μA |
| I_{DSS} | Drain-Source Leakage Current | $\text{V}_{\text{DS}}= 75\text{V}; \text{V}_{\text{GS}}= 0\text{V}; \text{T}_J=25^\circ\text{C}$ $\text{T}_J=125^\circ\text{C}$ | | | 1 10 | μA |
| V_{SDF} | Diode forward voltage | $\text{I}_{\text{SD}}=80\text{A}, \text{V}_{\text{GS}} = 0 \text{ V}$ | | | 1.5 | V |