



VOLTAGE RANGE: 50 - 1000V
CURRENT: 5.0 A

Features

- Diffused Junction
- Low Forward Voltage Drop
- High Current Capability
- High Reliability
- High Surge Current Capability

Mechanical Data

- Case: DO-201AD, Molded Plastic
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band
- Weight: 1.2 grams (approx.)
- Mounting Position: Any
- Marking: Type Number



DO-201AD		
Dim	Min	Max
A	25.40	—
B	8.50	9.53
C	0.96	1.06
D	4.80	5.21
All Dimensions in mm		

Maximum Ratings and Electrical Characteristics @ $T_A=25^{\circ}\text{C}$ unless otherwise specified

Single Phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Characteristic	Symbol	UF500	UF501	UF502	UF503	UF504	UF506	UF508	UF5010	Unit
Peak Repetitive Reverse Voltage	V_{RRM}									V
Working Peak Reverse Voltage	V_{RWM}	50	100	200	300	400	600	800	1000	V
DC Blocking Voltage	V_R									V
RMS Reverse Voltage	$V_{R(RMS)}$	35	70	140	210	280	420	560	700	V
Average Rectified Output Current (Note 1) @ $T_A = 55^{\circ}\text{C}$	I_o	5.0								A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	150								A
Forward Voltage @ $I_F = 5.0\text{A}$	V_{FM}		1.0			1.3		1.7		V
Peak Reverse Current @ $T_A = 25^{\circ}\text{C}$ At Rated DC Blocking Voltage @ $T_A = 100^{\circ}\text{C}$	I_{RM}					10				μA
						100				
Reverse Recovery Time (Note 2)	t_{rr}			50				75		nS
Typical Junction Capacitance (Note 3)	C_j			75				50		pF
Operating Temperature Range	T_j	-65 to +125								$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-65 to +150								$^{\circ}\text{C}$

- Note: 1. Leads maintained at ambient temperature at a distance of 9.5mm from the case
 2. Measured with $I_F = 0.5\text{A}$, $I_R = 1.0\text{A}$, $I_{RR} = 0.25\text{A}$. See figure 5.
 3. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.



FIG. 1 – TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 – TYPICAL REVERSE CHARACTERISTICS




FIG. 4 – MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 – TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 5 – TYPICAL JUNCTION CAPACITANCE

