



FCS-3303 Version: 1

Zoom Dome IP Network Camera, H.265, 3-Megapixel, 802.3af PoE, IR LEDs, 4.3X Optical Zoom

The LevelOne FCS-3303 Fixed Dome Camera offers a highly reliable, cost-effective IP surveillance solution in a low-profile dome casing which inhibits malicious tampering with the device. The IP camera offers 3-Megapixel resolution, and being PoE enabled, it can use a single Cat.5 cable to run both power and data, making deployments easy and flexible.

Key Features

- 3-Megapixel high-definition resolution
- Video compression: H.264, H.265
- Supports 4.3X optical zoom
- Built-in infrared LEDs for night viewing up to 20m
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Dual power support: 12V DC/PoE (IEEE 802.3af)
- Free surveillance and CMS (Central Management System) software packages with 64-channel license

Specifications

System Specifications

Standards & Protocols:

TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6

Image Sensor:

1/2.8" Progressive Scan CMOS

Lens:

Optical Zoom, f2.8-12mm, P-Iris

Port:

1 x RJ-45 10/100 Mbps PoE port
1 x Power Connector
1 x Audio:In/Out
1 x CVBS, BNC connector

Button/Knob:

Reset Button

**Indicator:**

Power

IR Cut Filter:

Removable infrared-cut filter for day & night function

IR LED:

20m

Angle of View:

90.6° - 32.7°

Video Compression:

H.265, H.264 , MJPEG

Resolution:

30 fps at 2048 x 1536

30 fps at 1920 x 1080

30 fps at 1280 x 720

30 fps at 800 x 600

30 fps at 640 x 480

30 fps at 320 x 240

Output Video Format:

AVI

Audio Compression:

G.711

Power Input:

DC 12V, PoE Class 3 (IEEE802.3af)

Power Consumption:

12.95 W (PoE)

Data Rate:

28Kbps - 20Mbps (per stream)

Storage Capacity:

MicroSDXC memory card slot (card not included) Up to 64 GB

Optical Zoom:

4.3X Optical Zoom

Features

General:

White Balance, Brightness, Contrast, Sharpness, Automatic gain control, Flickerless, Digital Image Stabilizer, Defogging

Security:

IP address filtering, HTTPS encryption, Password protected user level, Anonymous login

Management:

Notify control center, Change camera settings, Command other devices, E-mail notification with snapshots, Save video to local storage, Upload video or snapshot to FTP server, Activate external device through digital output

Video:

Video motion detection (3 regions), External device through digital input, Sound detection, Tampering detection, Simultaneous dual streams based on two configurations, Simultaneous dual streams, 4 Configurable regions for Privacy Mask.

Performance

Number of Clients:

16

Minimum illumination:

Color mode: 0.05 lux at F1.4 (AGC on), B/W Mode: 0.005 lux at F1.4 (AGC on)

Environment

Operating Temperature (°C):

-10°C ~ 40°C (14°F ~ 104°F)

Operating Humidity (Non-condensing):

20% - 80% RH

Physical Specifications

Dimensions (W x D x H mm):

124mm x 124mm x 119.35mm (4.88" x 4.70")

Weight (g):

500

Color:

White

Approval and Compliance

EMI/EMS:

CE,FCC

Others:

ONVIF

Others

Supported Browsers:

IE 9.0 or newer, Firefox with VLC, Chrome with VLC, Safari with QuickTime

Order Information

FCS-3303

Package Contents

FCS-3303

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Screw Kit

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.