

R46_310, Film, Metallized Polypropylene, Safety, 0.33 uF, 20%, 630 VDC, 310 VAC (X2), 110C, Lead Spacing = 15mm



| General Information | |
|---------------------|--------------------------|
| Supplier: | KEMET |
| Series: | R46_310 |
| Dielectric: | Metallized Polypropylene |
| Style: | Radial |
| Features: | EMI Safety |
| RoHS: | Yes |
| Lead: | Cut |
| Approvals: | ENEC, UL, cUL, CQC |
| AEC-Q200: | No |

| Dimensions | |
|------------|-----------------|
| L | 18mm +0.5mm |
| H | 12mm +0.1mm |
| T | 13mm +0.2mm |
| S | 15mm +/-0.4mm |
| LL | 4mm +2mm |
| F | 0.8mm +/-0.05mm |

| Specifications | |
|------------------------|--------------|
| Capacitance: | 0.33 uF |
| Capacitance Tolerance: | 20% |
| Voltage DC: | 630 VDC |
| Voltage AC: | 310 VAC (X2) |
| Temperature Range: | -40/+110C |
| Rated Temperature: | 110C |
| Dissipation Factor: | 0.1% 1kHz |
| Insulation Resistance: | 100 GOhms |
| Max dVdt: | 400 V |
| Safety Class: | X2 |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 750 |